TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

filed with the

STATE ENGINEER, SALEM, OREGON 33. The of OREGON 5. STATE ENGINEER, SALEM, OREGON 33. The oreginal of the control of the contr

WANTED WHIT DEDODE		Page 1
WATER WELL REPORT	NY 10 30	20 - 20C
TIME OF OREGON (Hase type or print)	State Well No.35	WL GU
(Hadse type or print)	State Permit No	
1978 not write above this line)	State Permit No	***************************************
13/0	· [7	

within 30 days from the date

MAY 25 1978 not write above this line)

WITTED DECOURAGE DEDE				
(1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:		_	
Name John Rayburn SALEM, CREGON	County Union Driller's well nu	mber	1	
Address Route 2, Bex 2670, LaGrande, Ore 97850		R. 39		E .W.M.
(a) TURN OF WORK (-bb).	Bearing and distance from section or subdivision	on corner		
(2) TYPE OF WORK (check):				
New Well Deepening Reconditioning Abandon Abandon				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 6			ft.
Rotary Driven Domestic Industrial Municipal	Static level 6 ft. below land s	urface. Da	te /-/	<u> 13-78</u>
Cable	Artesian pressure lbs. per square	e inch. Da	te	
CASING INSTALLED: Threaded □ Welded □ 16" Diam. from	(12) WELL LOG: Diameter of well be Depth drilled 349 ft. Depth of complete Formation: Describe color, texture, grain size a and show thickness and nature of each stratur with at least one entry for each change of format position of Static Water Level and indicate prince	eted well and structur n and aqui tion. Report	re of market pen	5 ft. aterials; netrated, hange in
ype of perforator used Machine	MATERIAL	From	То	SWL
Size of perforations 1/8 in. by 2 in.	Top soil	0	10	
6240 perforations from 90 ft. to 220 ft.	Sandy clay	10	33	
3120 perforations from 280 ft. to 345 ft.	Sandy clay and sandstone		49	
perforations from ft. to ft.	Sand and gravel		60	
	Sand coarse		70	
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Clay and wood chips		71	
Manufacturer's Name	Sand and elay		73	
Type	Clay green sandy	, , ,	75	
Diam. Slot size Set from ft. to ft.	Sandstone brown		80 83	
Diam. Slot size Set from ft. to ft.	Silty sand brown		91	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sand and gravel		97	
200 200 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Clay gray		.04	
Was a pump test made? W Yes □ No If yes, by whom? Farmore	Sand green		.06	
Yield: 1800 gal./min. with 87 ft. drawdown after 4 hrs.	Sand and gravel	106 1	.08	
, , , , , , , , , , , , , , , , , , , ,	Sand fine brown	108 1	16	
" " "	Clay breva		19	
Bailer test gal./min. with ft. drawdown after hrs.	Sand fine brown	119 1	28	
Artesian flow g.p.m.	Sand and gravel	128 1	35	
mperature of water Depth artesian flow encountered ft.	Work started 1/3/78 19 Complete	ed]/]	3/78	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1/1	3/78	19
Well seal—Material used	Drilling Machine Operator's Certification: This well was constructed under my Materials used and information reported best knowledge and belief. [Signed]	direct s above are	e true /23	to my
Brand name of bentonite	TW. A. TV. II Clander of the Constitution of t	1		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of water	This well was drilled under my jurisd true to the best of my knowledge and bel	iction and lief.	this r	eport is
Was a drive shoe used? Yes No Plugs Size: location ft.	NameSteveMoore(Person, firm or corporation)	······		
Did any strata contain unusable water? Yes No	D O D B M			
Type of water? depth of strata	Address P. O. Oramer P. Moses	axei	n.21.e	ا.دممد
Method of sealing strata off	[Signed] Stew Moore			
Was well gravel packed? ☑ Yes ☐ No Size of gravel: ♣-	(Water Well Cont	•		
Gravel placed from18 ft. to349 ft.	Contractor's License No 628 Date	5/23	•••••	, 197.8

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 (Please type or print) of well completion. The Completion of well completion.

State	Well No	
State	Permit No) .

1) OWNER: MAY 25 1978	(10) LOCATION OF WELL:	
Vame John Rayburn ATER RESOURCES DEPT.	County Union Driller's well nu	mber
Address Route 2, Box 2679 A Legrande Offe 97850	1/4 1/4 Section T.	R. W.M
	Bearing and distance from section or subdivision	n corner
(2) TYPE OF WORK (check):	Dearing and distance result section of the section	
New Well □ Deepening □ Reconditioning □ Abandon □		
f abandonment, describe material and procedure in Item 12.	(11) YELAMORD TENYINI . Commissed	-11
	(11) WATER LEVEL: Completed wo	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft
Rotary Driven Domestic Industrial Municipal Cable Detted	Static level ft. below land so	ırface. Date
Oug	Artesian pressure lbs. per square	inch. Date
CACING INCOALLED.		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	elow casing
"Diam, from	Depth drilled ft. Depth of comple	eted well ft
"Diam. from	Formation: Describe color, texture, grain size a	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum with at least one entry for each change of format	
) PERFORATIONS: Perforated? ☐ Yes ☐ No.	position of Static Water Level and indicate princ	
cype of perforator used	MATERIAL	From To SWL
	Sand fine gray	135 138
Size of periorations	Sandstone gray	138 141
perforations from	Clay hard brown	141 157
perforations from	Sand gray	157 164
perforations from ft. to ft.	Sandy clay	164 167
(7) SCREENS: Well screen installed? Yes No	Sand and clay	167 170
Manufacturer's Name	Sand and gravel	170 180
Type Model No	Sandstone soft brown	180 201
Diam Slot size Set from ft. to ft.	Sand gray coarse	201 214
Diam, Slot size Set from ft. to ft.	Clay hard gray	214 223
	Sandstone soft	223 232
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Clay brown and gray	232 260
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Clay hard brown	260 271
	Silty sand	271 275
Yield: gal./min. with ft. drawdown after nrs.	Sand brown	275 279
	Sand and gravel	279 290
" " " "	Clay gray	290 297
Bailer test gal./min. with ft. drawdown after hrs.	Sand and gravel	297 345
Artesian flow g.p.m.		
mperature of water Depth artesian flow encountered ft.	Work started 19 Complete	ed 19
(A) CONCERNICATION.	Date well drilling machine moved off of well	19
(9) CONSTRUCTION:	Drilling Machine Operator's Certification:	
Well seal—Material used	This well was constructed under my	direct supervision
Well sealed from land surface to ft.	Materials used and information reported	
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
Diameter of well bore below seal in.	[Signed](Drilling Machine Operator)	Date, 19
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	
Number of sacks of bentonite used in well seal sacks		· · · · · · · · · · · · · · · · · · ·
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdi	
of waterlbs./100 gals.	true to the best of my knowledge and bel	ief.
Was a drive shoe used? Yes No Plugs	Name(Person, firm or corporation)	(Type or print)
Did any strata contain unusable water? Yes No		
Type of water? depth of strata	Address	***************************************
Method of sealing strata off	[Signed]	·
Was well gravel packed? 🗌 Yes 🔲 No Size of gravel:	(Water Well Contr	actor)
Gravel placed from ft. to ft.	Contractor's License No Date	, 19
	IEETS IF NECESSARY)	SP*45656-11