

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion

MAR 24 1980

STATE OF OREGON
(Please type or print)

Range changed →
6/26/85 per W/M
State Well No. 35/39
State Permit No. 30ab

(1) OWNER:

Name Western States Land Company
Address 3571 Helms Drive
Jefferson, Oregon 97352

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Cable Driven Jettied Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal Irrigation Test Well Other

(5) CASING INSTALLED:

16" Diam. from +1 ft. to 163 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No
Type of perforator used Machine
Size of perforations 3/16 in. by 2 in.
432 perforations from 45 ft. to 54 ft.
528 perforations from 75 ft. to 86 ft.
1440 perforations from 125 ft. to 155 ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? Farmore
d: 572 gal./min. with 87 ft. drawdown after 24 hrs.
" " " " "
" " " " "
Ballor test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 26 in.
Diameter of well bore below seal 26 in.
Number of sacks of cement used in well seal 50 sacks
How was cement grout placed? pumped

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel: 3/8"
Gravel placed from 18 ft. to 165 ft.

(10) LOCATION OF WELL:

County Union Driller's well number #2
NW 1/4 NE 1/4 Section 30 T. 3 S. R. 38 E. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 9 ft.
Static level 9 ft. below land surface. Date 2/9/80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 26"
Depth drilled 165 ft. Depth of completed well 163 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	2	
Clay brown	2	15	
Clay blue	15	29	
Sand and gravel	29	34	
Clay blue and sand	34	37	
Clay blue	37	48	
Sand	48	54	
Clay brown	54	70	
Sandy clay gray	70	75	
Sand and gravel	75	86	
Clay brown	86	125	
Sand	125	130	
Clay and sand layers	130	148	
Sand and clay	148	155	
Clay	155	165	

Work started 2/8 19 80 Completed 2/9 19 80
Date well drilling machine moved off of well 2/9 19 80

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Steve Moore Date 3/21, 19 80
(Drilling Machine Operator)
Drilling Machine Operator's License No. 755

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Steve Moore
(Person, firm or corporation) (Type or print)
Address P. O. Drawer P, Moses Lake, Wa. 98837
[Signed] Steve Moore
(Water Well Contractor)
Contractor's License No. 628 Date 3/21, 19 80