NOTICE TO WATER WELL CONTRACTOR The original and first copy of this popular to be filed with the WATER RESOURCES DEPARTMENT 1979 STATE	VELL REPORT OF IVED OF OREGON SEP 24 1979 State Well No	35/3	?E -	34ba
	type or print) SEP 2 4 1979 tale wen No	· · · · · · · · · · · · · · · · · · ·	1	<u> </u>
SALEM, OREGON 97310 Within 30 days from the NESOURCES DEP! of well completion. (Ro not wri	type or print) te above the ATER RESOURCES THE Permit SALEM OREGON	No		***************************************
SALEM. OREGON	SALEM OREGON			
1.14.1966				
	(10) LOCATION OF WELL:			
Name Sherman E. Hawkins V	County Union Driller's well i	number		
Address Route 2, Box 2660	NE 14 NW 14 Section 34 T. 35	R. 39	Ε	W.M.
La Grande, Oregon 97850	Bearing and distance from section or subdivi	sion corner	•	
(2) TYPE OF WORK (check):				
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	— (11) WATER LEVEL: Completed	wall		
(3) TYPE OF WELL: (4) PROPOSED USE (check)		T		
Potory X Driven D	1F	0 /00 /00		
Cable	Static level 15 st. below land	surface. I	Date 9	/20/78
P Bored Irrigation Test Well Other	☐ Artesian pressure lbs. per squa	are inch. I	Date	
~) CASING INSTALLED: Threaded Welded M			•	
CASING INSTALLED: Threaded Welded 2 .6 "Diam. from +1 ft. to 201 ft. Gage • 250	(12) WELL LOG: Diameter of well	below casi	ng	26
	Depth drilled 215 ft. Depth of comp	oleted well	2	01 f t.
	Formation: Describe color, texture, grain size	and struct	ure of r	naterials:
" Diam. from	and show thickness and nature of each strat	um and aq	uifer pe	enetrated,
) PERFORATIONS: Perforated? 12 Ves Cl No.	with at least one entry for each change of form position of Static Water Level and indicate pr			
101101000 2 100		1		
Type of perforator used Machine	MATERIAL	From	То	SWL
Size of perforations 3/16 in. by 2 in.	Top soil		2	
936 perforations from 52½ ft. to	m. Clay white	2	6	
1344 perforations from 83 ft to 111	#. Clay brown	6		
336 150 157 157 tt. to 171	n. Clay gray	10	_ 22	
	Clay and sand layers	22	_25	
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Sand	25	33	
Manufacturer's Name	Sand and clay layers	33	45	
Type Model No	Clay	45	55	
Diam Slot size Set from ft. to	ft. Sand and graveland clay	55	_71	
Diam Slot size Set from ft. to	ft. Sand and clay	71	75	
(0) TEVET T. MECING. Drawdown is amount water level is	Sandy clay	75	80	
(8) WELL TESTS: Drawdown is amount water level is / 10/7	9 Sand and clay layers	80	106	
Was a pump test made? Z Yes No If yes, by whom? Courtrig		106	110	
000	rs. Clay brown and oray	110	120	
" "	" Clay green	120	150	
, <u> </u>	Sand brown	150	155	
" "	Sand clay and oravel	155	158	
Bailer test gal./min. with ft. drawdown after h	clay oray and brown	158	167	
an flow g.p.m.	Sand and prayel	167	191	
operature of water Depth artesian flow encountered	Llav oray and blue	191	215	19 5 5
		ted 1 5/2 9/2	<u>2U</u>	19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well	2/ 2	20	19 78
Well seal-Material used Neat cement	Drilling Machine Operator's Certification	:		
Well sealed from land surface to	This well was constructed under my			
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	. above a	re true	to my
Diameter of well bore below sealin.	[Signed]	Data	6/25	1079
Number of sacks of cement used in well seal50sac				
How was cement grout placed? Trimmied			155	
	Water Well Contractor's Certification:		٠,	
	This well was drilled under my jurisd		i this r	eport is
Was a drive shoe used? ☐ Yes 🍎 No Plugs Size: location	true to the best of my knowledge and be			•
	Name aceve moule			
Did any strata contain unusable water? Yes X No	(Person, firm or corporation) P. O. Drawer P, Moses	(Typ Lake:	e or prin	16) 18837
Type of water? depth of strata			w C .	, UUJ
Method of sealing strata off	- [Signed] Steve Moore	•		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:3/8"-	(Water Well Cont		••••••	•••••
Gravel placed from	Contractor's License No Date	6/2	25	., 19
				<u> </u>