

NOTICE TO WATER WELL OWNER
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED

JUN 23 1981

State Well No.

State Permit No.

SALEM, OREGON

(1) OWNER:

Name Eveline Parsons
Address Newport Ave. Imbler Oregon

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
" Diam. from 1 1/2 ft. to 5 7/8 ft. Gage 250

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

" " " "

Ball test 20 gal./min. with 28 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water 50 Depth artesian flow encountered ft.

CONSTRUCTION:

Well seal—Material used grout
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 9 sacks
How was cement grout placed? Pump

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☒ Yes ☐ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Union Driller's well number
SE 1/4 NW 1/4 Section 20 T.15 R. 39E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 30 ft.
Static level 11 ft. below land surface. Date May 23
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 60 ft. Depth of completed well 54 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	5	
SANDY CLAY BROWN	5	12	
CLAY BROWN	12	30	
SANDY CLAY	30	38	
SOME WATER			
CLAY BROWN	38	47	
SANDY MED	47	60	
WATER BEARING			11

RECEIVED

JUN 3 1981

WATER RESOURCES DEPT
SALEM, OREGON

Work started May 15 1981 Completed May 23 1981

Date well drilling machine moved off of well May 23 1981

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] A.C. Tandy Date May 23, 1981
(Drilling Machine Operator)

Drilling Machine Operator's License No. 6

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name A.C. Tandy (Type or print)
(Person, firm or corporation)

Address 14034 ave LeGrande, Oregon

[Signed] A.C. Tandy (Water Well Contractor)

Contractor's License No. 29 Date May 23, 1981