NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date of well completion.

Union 1440

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 4S/39E-13 da

State Permit No. .....

(1) OWNER:
Name TED GALLEGOS
Address 340½ S. 10th
UNION, ORE. 97883

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 110 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used TORCH
Size of perforations 3/32 in. by 7 in.
38 perforations from 90 ft. to 108 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 20 gal./min. with 55 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 52° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used PORTLAND CEMENT
Well sealed from land surface to 22 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 14 sacks
How was cement grout placed?
PUMPED THROUGH PIPE IN 10 IN. HOLE.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County UNION Driller's well number
NE ¼ SE ¼ Section 13 T. 4 So. R. 39E. W.M.
Bearing and distance from section or subdivision corner
APPROX. 1300 FT. WEST AND 1760 FT. NORTH OF THE SOUTHEAST CORNER OF SECTION 13

(11) WATER LEVEL: Completed well.
Depth at which water was first found 59 ft.
Static level 27 ft. below land surface. Date 8-27-80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 111 ft. Depth of completed well 111 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	5	
CLAY, BR. GRAVEL, LG.	5	13	
CEMENTED GRAVEL	13	18	
CLAY, BR.	18	25	
CLAY, BR. GRAVEL, LG.	25	59	
SAND, COARSE (W)	59	61	27
CLAY, BR. GRAVEL, MED.	61	105	
SAND, MED. (W)	105	107	27
CLAY, BR.	107	111	27

RECEIVED
SEP 15 1980
WATER RESOURCES DEPT
SALEM, OREGON

Work started AUG. 15 1980 Completed AUG. 27 1980
Date well drilling machine moved off of well AUG. 27 1980

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Ronald A. Moore (Drilling Machine Operator) Date SEPT. 2 1980
Drilling Machine Operator's License No. 913

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name MOORE WELL DRILLING (Person, firm or corporation) (Type or print)
Address RT 1 BOX 1 COVE, ORE. 97824
[Signed] Ronald A. Moore (Water Well Contractor)
Contractor's License No. 655 Date SEPT. 2, 1980

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119