NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

Union 1461

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 4S/40E-7CC

State Permit No.

(1) OWNER:
Name PHARIS TIMPY
Address BOX 353
UNION, ORE. 97883

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Large ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 81 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used TORCH
Size of perforations 1/8 in. by 7 in.
54 perforations from 55 ft. to 79 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 12 gal./min. with 30 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 53° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used PORTLAND CEMENT
Well sealed from land surface to 21 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 13 sacks
How was cement grout placed?
PUMPED THROUGH PIPE IN 10 IN. HOLE.

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County UNION Driller's well number
SW ¼ SW ¼ Section 7 T. 4 So. R. 40 E. W.M.
Bearing and distance from section or subdivision corner
APPROX. 170 FT. EAST AND 580 FT. NORTH OF THE SOUTHWEST CORNER OF SECTION 7

(11) WATER LEVEL: Completed well.
Depth at which water was first found 72 ft.
Static level 35 ft. below land surface. Date 9-22-80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 82 ft. Depth of completed well 82 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	4	
CLAY, BR. GRAVEL, LG.	4	34	
CLAY, BR.	34	42	
CLAY, BR. GRAVEL, LG.	42	72	
SAND, COARSE (W)	72	77	35
CLAY, BR. GRAVEL, LG.	77	82	35

RECEIVED
OCT 22 1980
WATER RESOURCES DEPT
SALEM, OREGON

Work started SEPT. 12 1980 Completed SEPT. 22 1980
Date well drilling machine moved off of well SEPT. 23 1980

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Ronald A. Moore (Drilling Machine Operator) Date OCT. 12, 1980
Drilling Machine Operator's License No. 913

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name MOORE WELL DRILLING (Person, firm or corporation) (Type or print)
Address RT 1 BOX 1 COVE, ORE. 97824
[Signed] Ronald A. Moore (Water Well Contractor)
Contractor's License No. 655 Date OCT. 12, 1980

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119