NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

MNC 1596

STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED JUN 23 1981 WATER RESOURCES DEPT SALEM, OREGON

State Well No. 1N/38E-27ac
State Permit No.

(1) OWNER:
Name Alven Renalds
Address Rt 1 Starns Road Summerville, Oregon

(2) TYPE OF WORK (check):
New Well ☐ Deepening ☒ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☐ glued
4" Diam. from 129 ft. to 209 ft. Gage SdR-21
" Diam. from PVC ft. to Pipe ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used saw
Size of perforations 1/8 in. by 6 in.
60 perforations from 178 ft. to 208 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 20 gal./min. with 81 ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 50 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
How was cement grout placed?
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Union Driller's well number
50 ¼NE ¼ Section 27 T. 1N R. 38E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 190 ft.
Static level 45 ft. below land surface. Date June 8
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing
Depth drilled 208 ft. Depth of completed well 205 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
GRAVELY CLAY GRAY	150	180	
CLAY GRAY	180	190	
GRAVEL med. SOME CLAY WATERBEARING	190	205	
CLAY GRAY	205	208	

Work started June 5 1981 Completed June 8 1981
Date well drilling machine moved off of well June 8 1981

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] O.C. Tandy (Drilling Machine Operator) Date June 8, 1981
Drilling Machine Operator's License No. 6

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name O.C. TANDY (Person, firm or corporation) (Type or print)
Address 1403 4th ave LaGrande, Oregon
[Signed] O.C. Tandy (Water Well Contractor)
Contractor's License No. 29 Date June 8, 1981

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119