STATE OF OREGON EXPLANA 13 1986

WATER WELL REPORT
(as required by ORS 537.76 ATER RESOURCES LDERTYPE or PRINT IN INK

UNIO

3N/40E-18 Remb (for official use only)

SALEM ORECON	(for official use only)
(1) OWNER:	(10) LOCATION OF WELL by legal description:
Name Oregon Dept. of Fish & Wildlife	County Union 4 4 of Section 18
Address 506 S.W. Mill Street	Township 3N Range 40E , WM
City Portland, State Oregon	(Township is North or South) (Range is East or West)
97207	Tax Lot Lot Block Subdivision
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address) Lookingglass
New Well Deepening Reconditioning Abandon D	Hatchery
If abandonment, describe material and procedure in Item 12.	Test Well Bl
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:
Rotary Air Driven Domestic Industrial Municipal	Depth at which water was first found # ft
Thermal:  Rotary Mud  Dug  Irrigation  Withdrawal  Reinjection	Static level # ft. below land surface. Date
Other:	Artesian pressure ——— lbs. per square inch. Date ——
C Le Bored Piezometric I Grounding Test	(12) WELL LOG: Diameter of well below casing
S) CASING INSTALLED: Unchanged Plastic	(12) WELL LOG: Diameter of well below casing
Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness
ft. Gauge	and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal
ft. Gauge	water-bearing strata.
LINER INSTALLED: Steel  Plastic	NAMEDIAL BUILDING
+1 294 Threaded Welded	MATERIAL From To SWL
1	well was originally reported to have been deepened by A.M. Jannsen Well
(6) PERFORATIONS: Perforated?   Yes   No	Drilling in 1985 to 528'
Size of perforations in. by in.	Drilling in 1905 to 520 5
perforations from ft. to ft.	We sounded well at 516': installed
perforations from	
ft. to	
	attached sketch.
(7) SCREENS: Well screen installed?  Yes  No	
Manufacturer's Name Hydrophillic	* Pinnacle Geotechnical installed
Type Piezometer Tips Model No.	
Diam. 11 Slot Size • 010 Set from 294 ft. to 296 ft.	instruments tomeasure and record
Diam. 11/2 Slot Size • 010 Set from 510 ft. to 512 ft.	water levels - data was not collected
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	by constructor.
- Described to the second seco	
Was a pump test made?  Yes No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
Air test gal./min. with drill stem at ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
nperature of water Depth artesian flow encounteredft.	Date work started 11/19/85 /completed 11/22/85
(9) CONSTRUCTION: Special standards: Yes \( \sigma \) No \( \sigma \)	Date well drilling machine moved off of well 11/22 19 85
Well seal—Material used	
Well sealed from hand surface to ft.	(unbonded) Water Well Constructor Certification (if applicable):
Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	1 79
Amount of sealing materialsacks pounds	[Signed] Undld & Dave 1-10, 19 80
How was cement grout placed?	(bonded) Water Well Constructor Certification:
	BondEX490-652 Issued by: American States Ins.
	(number) (Surety Company Name)
Was pump installed? Type HP Depth ft.	On behalf of Schneider Equipment, Inc.  (type or print name of Water Well Constructor)
Was a drive shoe uses?   Yes No Plugs Size location ft.	(type or print name of water wen constructor)
Did any strata centain unusable water?	This well was drilled under my jurisdiction and this report is true to the
Type of Water? depth of strata	best of my knew toge and belieft
Method of sealing strata off	(Signed) Stephen Stephen
Was well gravel packed? Yes No Size of gravel: Pea	(Water Well Constructor)
Gravel placed from See ft. to Sketch ft.	(Dated)