of this report are to be	L RERECEIVED	1<13	Page	i Kof
STATE OF	OREGON DEO-61979 State Well No.	1-1-1-	.12	129
within 30 days from the date of well completion.	ove WATER RESOURCES DEFT Permit N SALEM, OREGON	. <u>C</u>	5-71	65
(1) OWNER: 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	(10) LOCATION OF WELL:	• .		
Name Doyle Ricininger WATER RESOURCES DEPARTMENT	County Union Driller's well no	umber	_1	
Address Imbler, Oregon SALES DEPT	SE 14 SW 14 Section 9 T. 1S	R.,	<u> 39 E.</u>	W.M.
	Bearing and distance from section or subdivisi	or corne	r ·	
(2) TYPE OF WORK (check):				
New Well ■ Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	70 <b>11</b>		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	_ `. ·	CII.	16	
	Depth at which water was first found		*****	<u>n.</u> ,
Rotary Driven Domestic Industrial Municipal	Static level 16 ft. below land a	surface.	Date	
□ Bored □ Irrigation □ Test Well □ Other □	Artesian pressure lbs. per squar	re inch.	Date	
(F) CACING INCHALLED.				26"
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	below car	sing	
16 "Diam from +1 tt. to 465 ft. Gage 250	Depth drilled 465 ft. Depth of compl	leted wel	1 46	5 ft.
	Formation: Describe color, texture, grain size	and struc	ture of m	aterials;
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratu			
'S) PERFORATIONS: Perforated? [X Yes [] No.	with at least one entry for each change of forma position of Static Water Level and indicate prin			
Maabiaa	MATERIAL	From	то	SWL
7/16		+	<del>                                     </del>	
Size of perforations 3/16 in. by 2 in.	Top soil	<u>0</u>	3	
6240 perforations from 285 ft. to 415 ft.	Clay soft	3	36	
perforations from ft. to ft.	Clay blue	36	44	
perforations from ft. to ft.	Clay blue & sand	44	82	
(7) COPPING.	Clay brewn	82	85	
(7) SCREENS: Well screen installed?   Yes   No	Clay sandy	85	97	
Manufacturer's Name	Clay soft gray	97	129	
Type Model No.	Clay green and gray	129	135	
Diam. Slot size Set from ft. to ft.	Clay green	135	160	
Diam. Slot size Set from ft. to ft.	Sandstone	160	170	
(8) WELL TESTS: Drawdown is amount water level is	Clay gray	170	180	
lowered below static level	Clay green & gray layers	180	200	
a pump test made? No If yes, by whom? Farmore	Clay gray	200	210	<del> </del>
raid: 250 gal./min. with 290 ft. drawdown after 4 hrs.	Clay gray and brown	210	239	
" " " "	Clay green	239	255	
Jn " " "	Clay brown and green	255	265	
	Sandstone and clay	265	275	
Poller test gal./min. with ft. drawdown after hrs.	Clay gray	275	283	<del></del>
sian flow g.p.m.	Sandatone and gravel	283	287	<del></del>
emperature of water Depth artesian flow encountered ft.	Work started 10/29 19 77 Complet	ed	11/1	19 77
(A) GOVERNIGHTON	Date well drilling machine moved off of well		11/1	19 77
(9) CONSTRUCTION:	D III - M. Constants Continued to			
Well seal—Material used Neat cement	Drilling Machine Operator's Certification: This well was constructed under my		enner	vieion
Well sealed from land surface toft.	Materials used and information reported			
Diameter of well bore to bottom of seal	best knowledge and belief.		216	~B
Diameter of well bore below sealin.	[Signed] Morum (Drilling Machine Operator)	Date	2/0	, 19
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.		755	
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's License No.			
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons		iation c	nd this -	anort is
of water lbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and bel	icuon al lief.	na wits F	shore 12
Was a drive shoe used? ☐ Yes 🞽 No Plugs Size: location ft.	Name Steve Hecre			
Did any strata contain unusable water?   Yes  No	(Person, firm or corporation)		ype or prir	_
Type of water? depth of strata	Address P. O. Drawer P, Hoses I	ake,	Wa. 95	ō <u>37</u>
Method of sealing strata off	I m of more			
Was well gravel packed? ■ Yes □ No Size of gravel: 3/8"-	[Signed] (Water Well Cont	ractor)		**********
Gravel placed from	Contractor's License No628 Date	*********	2/6	., 19.76
was a province of the contract	,			

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT CEIVEN well No. 5398-9 ca

(Please type or print)

		******	•••••	
•	' ~		0	_
	· ( \ -	71	45	>
Ο.		!		•••••

	,	-		7 7	C 5					0 1973	State Peri
,	1 12	1	(Do	pot	write	alpeive	this	line)	FR 100 (7) (7)	URCES	
44	تناسيا	<b>C</b> 3	-	ti i	t. L.	g <b>L</b> ande	W	AIER	RESO	URCES	DEPT

•	i ne	-0	197	State	Permit	No
line)						

10	
11111	120
	UD
WVW/	7U

(1) OWNER: 4.1979	(10) LOEATION OF WOLL:	•
	County Union Driller's well no	umber 1
Address Tabler Oregon MALER REDUCTION	SE 34 SW 34 Section 9 T. 1S	R., 39 E. W.M.
SALEM OFFICEN	Bearing and distance from section or subdivisi	
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivisi	on comer
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.		••
	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	<u>ft.</u>
Rotary Driven Domestic Industrial Municipal Domestic	Static level ft. below land s	surface. Date
Cs de	Artesian pressure lbs. per squar	re inch. Date
(5) CASING INSTALLED: Threaded  Welded	(12) WELL LOG: Diameter of well 1	below casing
	Depth drilled ft. Depth of compl	leted well ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size	and structure of materials:
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratu	m and aquifer penetrated,
(c) DEDEODATIONS.	with at least one entry for each change of forma position of Static Water Level and indicate prin	
(6) PERFORATIONS: Perforated?   Yes   No.		
pe of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Sandy clay & sandstone	287   290
perforations from ft. to ft.	Sand, sandstone and clay	290   298
perforations from ft. to ft.	Clay dark gray	298 311
perforations from ft. to ft.	Sandy clay green	311 314
(E) SCREENS.	Sand w/traces of clay	314 321
(7) SCREENS: Well screen installed?   Yes   No	Clay gray	321 323
Manufacturer's Name	Sandstone and gray clay	323 327
Type Model No	Clay green	327 329
Diam. Slot size Set from ft. to ft.	Sandstone and clay	329 331
Diam. Slot size Set from ft. to ft.	Sand and clay	331 360
(8) WELL TESTS: Drawdown is amount water level is	Clay brown and green	360 366
lowered below static level	Sand brown	366 367
Was a pump test made?   Yes   No If yes, by whom?	Clay gray	367 375
had: gal./min. with ft. drawdown after hrs.	Sand coerse white	371 381 381 391
н и и	Sand and clay layers	
, n n n	Clay gray	391 405 405 410
Bailer test gal./min. with ft. drawdown after hrs.	Sand white and clay	410 420
sian flow g.p.m.	Clay gray	420 465
	Clay hard green	
emperature of water Depth artesian flow encountered ft.	Work started 19 Complet	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	19
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my	
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief.	above are true to my
Diameter of well bore below sealin.	_	Date 19
Number of sacks of cement used in well sealsacks	[Signed](Drilling Machine Operator)	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	***************************************
Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water	This well was drilled under my jurisd	iction and this report is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and bel	
Did any strata contain unusable water?  Yes No	Name (Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address	
Method of sealing strata off	[Signed](Water Well Conti	
Was well gravel packed?   Yes   No Size of gravel:		
Gravel placed from ft. to ft.	Contractor's License No Date	, 19