NOTICE TO WATER WELL CONTRACTOR The original and fitte port of this report are tracked filed with the JUL 2 4 1973

TATER WELL REPORT

STATE OF OREGON

UNIO State Vell No. 45/39E-10
2363 State Permit No.

	The state of the s
(1) OWNER:	(10) LOCATION OF WELL:
Name DAVID RAUM	County () () Driller's well number
Address LAGRANDE, ORE	1117 30 -
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Lary 1980 N \$ 30 E - of 5 W
New Well ⚠ Deepening ☐ Reconditioning ☐ Abandon ☐	COLNER OF TONE
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
	Depth at which water was first found 42 ft.
Cable	Static level 5 ft. below land surface. Date
Dug ☐ Bored ☐ Irrigation ▼ Test Well ☐ Other ☐	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 97/r
16 "Diam from O ft to 437 ft Gage -25	
" Diam. from ft. to ft. Gage	
ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated.
PERFORATIONS: Perforated? W Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used FACTORY DERF.	
Size of perforations 1/5 in. by 3 in.	MATERIAL From To SWL
4160 perforations from 40 ft. to 180 ft.	[10psoi] 0 3
perforations from Z Z A ft. to 2.70 ft.	CRAY CIAY SZY
2560 perforations from 350 ft. to 930 ft.	Raylders 5 has 1 50 17
	Clay braws 72 21
(7) SCREENS: Well screen installed? Yes No	Cuare arayes 81 120
Manufacturer's Name	Rxx 10/04 110/19
Type Model No.	Gravel & grarse sand 119 184
Diam. Slot size Set from ft. to ft.	B/vec/ay /24 220
Diam. Slot size Set from ft. to ft.	medrum stand 220 270
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Bluerlay send streeks 270 346
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	Medium to fine sand 345 429
774-1-4	Blue croy, sand streaks 429 500
Yield: gal./min. with ft. drawdown after hrs.	
H	
Bailer test 1 d d gal/min with 1 2 ft drawdown after 6 hrs	The state of the s
Bailer test / d \(\partial \text{gal./min. with 1 Z ft. drawdown after 6, hrs.} \)	The second secon
Artesian flow g.p.m.	
perature of water 54 Depth artesian flow encounteredft.	Work started Apr 23 1973 Completed June 3 1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well Juke 5 1973
Well seal-Material used CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal 2.4 in.	best knowledge and belief.
Diameter of well bore below sealin.	[Signed] & Carriel Date 1/1 , 19 23
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 388
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water lbs./130 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	NameCO RRIELL & SEDGWICK, INE (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address BUX 613 LAGRANDE ORE.
Method of sealing strata off	AAD 12
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from 2.0 ft. to 4.3.0 ft.	A CONTROL OF THE PROPERTY OF T
16.	Contractor's License No. 2/ Date 7/ 19/3