NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

UNIO 2399

State Well No. 1N/38E-26cb
State Permit No.

(1) OWNER:
Name Claton Long
Address P.O. Box 533 Elgin, Oregon

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
20" Diam. from +1 ft. to 79 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Torch
Size of perforations 1/8 in. by 6 in.
18 perforations from 50 ft. to 60 ft.
15 perforations from 70 ft. to 80 ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 14 gal./min. with 32 ft. drawdown after ✓ hrs.
Artesian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 11 sacks
How was cement grout placed? grout-Pump

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Union Driller's well number
NW ¼ SW ¼ Section 26 T. 1 N R. 38 E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found ft.
Static level 38 ft. below land surface. Date June 23
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing
Depth drilled 91 ft. Depth of completed well 96 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOPSOIL	0	3	
CLAY BROWN	3	14	
GRAVELY CLAY	14	46	
GRAVEL MED. CLAY	46	63	
-BROWN			
SANDY CLAY	63	67	
LITTLE WATER.			
GRAVELY CLAY	67	82	
SAND MED.	82	87	
WATER BEARING			
GRAVELY CLAY	87	91	

RECEIVED
JUL 27 1979
WATER RESOURCES DEPT
SALEM, OREGON

Work started June 19 1979 Completed June 23 1979
Date well drilling machine moved off of well " 23 1979

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] O.C. Tandy Date June 24, 1979
(Drilling Machine Operator)
Drilling Machine Operator's License No. 6

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name O.C. Tandy
(Person, firm or corporation) (Type or print)
Address 14034 Ore La Grande, Oregon
[Signed] O.C. Tandy
(Water Well Contractor)
Contractor's License No. 29 Date June 24, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119