UNIO 51722

STATE OF OREGON

WATER SUPPLY WELL REPORT

(as required by ORS 537.765)

WELL I.D. # L 78290

Uni?

START CARD # 175647

Instructions for completing this report are on the last page of this form.					
(1) LAND OWNER Well Number	(9) LOCATION County UNION	OF WELL (legal	description	ı)	
Address 725 SUMMER ST. NE SUITE C	Tax Lot		Lot		
City SALEM State OR Zip 97301-1266	Township 5	s	Range 41	E	WM
	Section 6				1/4
(2) TYPE OF WORK Z New Well Deepening Alteration (repair/recondition) Abandonment Conversion	Lat° Long°				
(3) DRILL METHOD	Street Address of W		ss) <u>8 Miles</u>	SOUTH OF	
(4) PROPOSED USE Domestic Ø Community Industrial Irrigation Thermal Injection Livestock Other		ATER LEVEL _ ft. below land surfa _ ft. below land surfa		ate 2-7-06	
(5) BORE HOLE CONSTRUCTION Special Construction: Yes V No Depth of Completed Well 165 ft.	Artesian pressure		are inch Da	ate	
Explosives used: 🔲 Yes 💋 No Type Amount	(11) WATER BE Depth at which wate)		
	-				
BORE HOLE SEAL Diameter From To Material From To Sacks or Pounds	From	То		d Flow Rate	SWL
Diameter From To Material From To Sacks or Pounds 12 0 12 CEMENT 105 0 65	12	15	5GPM		6
	65	75	40GPM		6
10 23 105	<u>125</u>	145	85GPM		1
8 105 165			1		<u> </u>
How was seal placed: Method A Ø B C D E	(12) WELL LOG	Grou	d Elevation _		
Backfill placed from ft. to ft. Material	Mat	erial	From	То	SWL
Gravel placed from ft. to ft. Size of gravel	SOIL		0	2	
	BROWN CLAY, C	GRAVEL, SAND	2	9	
(6) CASING/LINER		T, BROWN CLAY	9	19	6
Diameter From To Gauge Steel Plastic Welded Threaded	FRAC BASALT,		<u>19</u>	34	<u> </u>
Casing: 8 +1.5 101 0.25 Z 🛛 📿 Z	FRAC BASALT,		34	48	1
	FRAC BASALT,		48	63	<u> </u>
	FRAC BASALT,		<u>63</u>	75	6
Liner: 6 85 165 0.25 2	FRAC BASALT,		75	87	
	BLACK BASALT		87	112	
	FRAC BASALT,		122		
Drive Shoe used 🔲 Inside 🔲 Outside 💋 None Final location of shoe(s)					4 2006
				FEB 1 4	2000
(7) PERFORATIONS/SCREENS					
Perforations Method TORCH				ER RESOI	RCES DEP
Screens Type Material	Date Started 12-27	- 05 Co	mpleted 2-6	GALEM, C	REGON
From To Slot Number Diameter Tele/pipe Casing Liner					
Size size	(unbonded) Water	work I performed of		tion desperie	na alteration as
125 145 1/4X4 25 6	abandonment of this				
H	construction standar				
	the best of my know	ledge and belief.		-	
			_		
	WWC Number		Date		
(8) WELL TESTS: Minimum testing time is 1 hour ☑ Pump □ Bailer ☑ Air □ Flowing Artesian	Signed				
Yield gal/min Drawdown Drill stem at Time	(bonded) Water W	ell Constructor Ce	tification		
70+ <u>150</u> 1HR	I accept respons	ibility for the constru	iction, deeper		
85 107 24HR	abandonment work				
	above. All work per				
Temperature of water 55 Depth Artesian Flow Found	supply well construct	ction standards. This	report is true	e to the best of	t my knowledge
Was a water analysis done? Yes By whom	and belief.				
Did any strata contain water not suitable for intended use?	WWC Number_ 177	75	Date 2-8	8-06	
Did any strata contain water not suitable for intended use? □ 100 little www.c.Nuitoet 175					
	Signed	aport.	to	togle	te
Depth of strata:			ZT1		

FIRST COPY - CONSTRUCTOR

SECOND COPY ~ CUSTOMER 06/16/2004

EARTH & WATER WORKS, INC. 10202 Valley Ave. * Island City, OR 97850* 541-963-2244 CCB#142427 WWC#1775 MWC#10509

PUMP TEST

.

PUMP DEPTH SET-	130FT				
PUMP USED-	70GPM 5HP				
STATIC MEASURED AT GROUND LEVEL					

TIME		FLOW (GPM)	COMMENTS
1:20	1.0		START
1:22		103	
1:24			GOOD CLEAN WATER
1:26		101	
1: 28		99	
1:30		98	
1:35		97	
1: 40		96	
1: 4 5		96	
1:50		95	
1:55		9 5	
2: 0 0		94	
2:15		94	
2:30		93	
2:45		93	
3:00		93	
3: 30		92	
4:00		91	
5:00		90	
6:00		89	
7:00		89	
8:00		88	
9:00		87	
10:00		87	
11:00		87	#
12: 00			STATIC HAS LEVELED OFF
1:00		86	•
2:00		86	
3:00		86	
4:00		86	
5:00		86	
6:00		86	
7:00		86	
8:00		86	
9:00			DISINFECT WELL
10:00		86	
11:00		86	
12: 0 0			TAKE SAMPLES TO BE TESTED
1:20	100.0	86	STOP

