UNIO 52812

STATE OF OREGON
WATER SUPPLY WELL REPORT
(as required by ORS 537.765 & OAR 690-205-0210)

		Page 1 of 2
WELL I.D. LABEL# L	131376	_
START CARD#	1043830	
ORIGINAL LOG#	UNION	52714

(1) LAND OWNER Owner Well I.D.	
First Name SAM Last Name BAKER	(9) LOCATION OF WELL (legal description)
Company	County UNION Twp 4.00 S N/S Range 40.00 E E/W W
Address 59257 HIGH VALLEY RD.	Sec 22 SW 1/4 of the NW 1/4 Tax Lot 4501
City UNION State OR Zip 97850	
(2) TYPE OF WORK New Well Deepening Conversion	Tax Map Number Lot Lat " " or DMS or DD
Alteration (complete 2a & 10) Abandonment(complete 5a)	
(2a) PRE-ALTERATION	Long or DD DMS or DD Street address of well Nearest address
Dia + From To Gauge Stl Plstc Wld Thrd Casing: 8 X 2 42 0.25 X X Image: Stl <	59257 HIGH VALLEY RD., UNION, OR 97850
Material From To Amt sacks/lbs	1 39237 FIGH VALLET RD., UNION, OR 97830
Seal: Bentonite Chips 0 420 10750 Pounds	
(3) DRILL METHOD	(10) STATIC WATER LEVEL
Rotary Air Rotary Mud Cable Auger Cable Mud	Date SWI (nsi) + SWI (ft)
Reverse Rotary Other	Existing Well / Pre-Alteration 7/25/2019 22 X 50.8
	Completed Well 1/17/2020 82 X 189.4
(4) PROPOSED USE Domestic X Irrigation Community	Flowing Artesian? Dry Hole?
Industrial/ Commericial Livestock Dewatering	WATER BEARING ZONES Depth water was first found 277.00
Thermal Injection Other	SWL Date From To Est Flow SWL(psi) + SWL(ft)
(5) BORE HOLE CONSTRUCTION Special Standard X (Attach copy	d / =()
	1130/2013
Depth of Completed Well 590.00 ft. BORE HOLE SEAL sacks/	7/30/2019 386 392 40 34
BORE HOLE SEAL sacks/ Dia From To Material From To Amt lbs	9/11/2019 555 600 400 82
23 0 15 Bentonite 0 8 8 S	
19 15 30 Calculated 5	·
16 30 432 Cement with 3% Bento 8 432 234 S	(11) MARKA A O.C.
12 432 600 Calculated 170	(11) WELL LOG Ground Elevation
How was seal placed: Method XA BXB CDD E	Material From To
X Other POURED DRY	REFERENCE WELL LOG 0 100
Backfill placed from ft. to ft. Material	UNIO 52714 100 200
Filter pack from ft. to ft. Material Size	WELL ID 131376 200 300
Explosives used: Yes Type Amount	START CARD 1039853 300 600
(5a) ABANDONMENT USING UNHYDRATED BENTONITE Proposed Amount Actual Amount	
(6) CASING/LINER	
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	RECEIVED
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	
	FEB 4 2020
Shoe Inside Outside Other Location of shoe(s)	
	OWRD
Temp casing Yes Dia From + To	
(7) PERFORATIONS/SCREENS	
Perforations Method	D-4- 944-1705/0010
Screens Type Material Perf/ Casing/ Screen Scrn/slot Slot # of Tele/	Date Started 7/25/2019 Completed 1/17/2020
Screen Liner Dia From To width length slots pipe size	(unbonded) Water Well Constructor Certification
	I certify that the work I performed on the construction, deepening, alteration, or
	abandonment of this well is in compliance with Oregon water supply we
	construction standards. Materials used and information reported above are true to
	the best of my knowledge and belief.
	License Number Date
(8) WELL TESTS: Minimum testing time is 1 hour	Signed
Pump Bailer • Air Flowing Artesian	Signed
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) Water Well Constructor Certification
225 0 0 1	I accept responsibility for the construction, deepening, alteration, or abandonme
300 36 380 1	work performed on this well during the construction dates reported above. All we
350 195	performed during this time is in compliance with Oregon water supply w
Temperature 63 °F Lab analysis Yes By	construction standards. This report is true to the best of my knowledge and belief
Water quality concerns? Yes (describe below) TDS amount 77 ppm	License Number 1775 Date 2/5/2020
From To Description Amount Units	
	Signed JASON ACQUISTAPACE (E-filed)
	Contact Info (optional)

WATER SUPPLY WELL REPORT - continuation page

WELL I.D. LABEL# L	131376	
START CARD #	1043830	
ORIGINAL LOG#	UNION	52714

	ONIGH (THE EOG III CINION	32714
2a) PRE-ALTERATION	Water Quality Concerns	
Dia + From To Gauge Stl Plstc Wld Thrd	From To Description	Amount Units
	To Bescription	
Material From To Amt sacks/lbs		
Cement 420 432 565 Pounds		
420 432 503 Founds		
132 137 000 Tourido		
5) BORE HOLE CONSTRUCTION	(10) STATIC WATER LEVEL	
	SWL Date From To Est Flow	SWL(psi) + SWL(ft)
BORE HOLE SEAL sacks/ Dia From To Material From To Amt lbs		,
Dia From To Material From To Amt lbs		
Cement 385 468 45 S		
Calculated 20		
Cement with 3% Bento	,	——————————————————————————————————————
Calculated 50		
Calculated		
·		
Calculated		
FILTER PACK	(4) WELL LOC	
From To Material Size	(11) WELL LOG	
	Material	From To
CACINICA INED		
) CASING/LINER -		
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd		
) PERFORATIONS/SCREENS		
Perf/ Casing/ Screen Scrn/slot Slot # of Tele/		
Screen Liner Dia From To width length slots pipe size	<u></u>	
	-	
	-	
	1	
	1	l
	-	
- 	Comments/Remarks	
	-	
(2) WELL TESTS: Minimum testing time is 1 hour	8"x 12" reducing cone on top of 8" casing	
(8) WELL TESTS: Minimum testing time is 1 hour		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)		
600 (380 1		
380 1	` 	
	11	