

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

UN10
546

WATER WELL REPORT

STATE OF OREGON
(Please type or print)

RECEIVED

SEP 02 1980

State Well No. 15/30E-33CA

(Do not write above this line)

WATER RESOURCES DEPT
SALEM, OREGON

State Permit No.

(1) OWNER:

Name James E. Klein
Address Box 3202 La Grande, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
 Jetted
 Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

6" Diam. from 1 ft. to 130 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No
Type of perforator used Torch
Size of perforations 5/8 in. by 6 in.
70 perforations from 30 ft. to 110 ft.
30 perforations from 110 ft. to 130 ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
 a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Boiler test 30 gal./min. with 77 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 24 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 17 sacks
How was cement grout placed? grout pump
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Union Driller's well number
NE 1/4 SW 1/4 Section 33 T. 15 R. 38E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 28 ft.
Static level 28 ft. below land surface. Date 8/4
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 130 ft. Depth of completed well 130 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	3	
GRAVEL COARSE	3	12	
CLAY			
GRAVEL COARSE	12	28	
CEMENTED			
GRAVEL SMALL	28	30	
SOM WATER			
GRAVEL COARSE	30	78	
CLAY			
GRAVELY CLAY	78	95	
WATER ON TOP OF CLAY			
GRAVEL COARSE	95	107	
CLAY BROWN			
GRAVEL Med.	107	130	
Water bearing			

Work started 7/23 1980 Completed 8/4 1980
Date well drilling machine moved off of well 8/4 1980

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] O.C. Tandy Date 8/10, 80
(Drilling Machine Operator)
Drilling Machine Operator's License No. 6

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name O.C. Tandy (Type or print)
(Person, firm or Corporation) (Type or print)
Address 1403 Home La Grande, Ore
[Signed] O.C. Tandy
(Water Well Contractor)
Contractor's License No. 29 Date 8/10, 1980