

RECEIVED

Union 769 Union 769

35/38E-30d

STATE OF OREGON WATER WELL REPORT (as required by ORS 537.765)

OCT 30 1985

WATER RESOURCES DEPT SALEM, OREGON PLEASE TYPE or PRINT IN INK

(for official use only)

(1) OWNER:

Name LDS CHURCH 3rd & 4th WARD Address COVE & McALLISTER RT City LA GRANDE State ORE

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

(3) TYPE OF WELL:

Rotary Air [X] Driven [] Cable [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Thermal: Irrigation [X] Withdrawal [] Rejection [] Other: Piezometric [] Grounding [] Test []

(5) CASING INSTALLED:

6" Diam. from +1 ft. to 266 ft. Gauge .280

LINER INSTALLED:

5"00 Diam. from 252 ft. to 312 ft. Gauge 188

(6) PERFORATIONS:

Size of perforations 116 in. by 9 in. 60 perforations from 282 ft. to 312 ft. 450 perforations from 140 ft. to 180 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [X] No If yes, by whom? Air test 40 gal./min. with drill stem at 200 ft. 1 hrs. Bailer test Artesian flow g.p.m. Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes [] No [X] Well seal—Material used Cement Well sealed from land surface to 20 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Amount of sealing material 14 sacks [X] pounds [] How was cement grout placed? PUMPED FROM BOTTOM UP Was pump installed? NO Type HP Depth ft. Was a drive shoe used? [X] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No Type of Water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL by legal description:

County UNION SE 1/4 SW 1/4 of Section 3 Township 35 Range 38E WM. Tax Lot Lot Block Subdivision

MAILING ADDRESS OF WELL (or nearest address)

CORNER COVE & McALLISTER

(11) WATER LEVEL of COMPLETED WELL:

Depth at which water was first found 8 ft. Static level 25 ft. below land surface. Date Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6 Depth drilled 320 ft. Depth of completed well 320 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: TOP SOIL, M GRAVEL & SAND, COARSE SAND WB, GRAVEL & SAND, COARSE SAND & GRAVEL, GRAVEL & TAN CLAY, MEDIUM GRAVEL, COARSE SAND.

Date work started 7-14-85 / completed 9-25-85 Date well drilling machine moved off of well 9-27-85 19

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] John D McNally Date 10-20-85

(bonded) Water Well Constructor Certification:

Bond 00665-718 Issued by: USFG (number) (Surety Company Name) On behalf of JOHN D MCNALLY (type or print name of Water Well Constructor)

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief:

(Signed) John D McNally (Water Well Constructor) (Dated) 10-20-85