NOTICE TO WATER WELL CONTRAC The original and first copy of this report are to be filed with the

Juio 940

TECEIVED WATE 910

SEP 23 1988 to DI No. 3/38-5 J

state engineer, salem, oregon 97310 A 1 2 A 1 (Please type or print) within 30 days from the date CREE type or principal ATE ENGINEER t No. of well completion. SALEM OREGON

(1) OWNER:	(11) LOCATION OF WELL:		
Name Boise Cascade Corp.	County Union Driller's well nu	ımber 134	
Address P.O. Box 200 Boise Idaho	NE 14 SE 14 Section 5 T. 38	R. 38E	W.M.
(0) TYPE OF WORK (short).	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	495' South 990' West 1 Section of		
New Well Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 12.	Corner of Sections 4&5		
(3) TYPE OF WELL: (4) PROPOSED USE (check):			
Rotary Driven Domestic Industrial Municipal	(12) WELL LOG: Diameter of well below casing		
Cable Jetted Irrigation Test Well Other	Depth drilled 1000 ft. Depth of comple	eted well 10	00 ft.
	Formation: Describe color, texture, grain size a		
CASING INSTALLED: Threaded Welded \$12&29	and show thickness and nature of each strature with at least one entry for each change of forms	-	•
Diam. from the to gage	in position of Static Water Level as drilling pro		
16" Diam. from 490 ft. to 630 ft. Gage 312	MATERIAL	From To	SWL
12" Diam. from 617 ft. to 1000 ft. Gage 344	Cemented Gravel Brown	62 102	2 121
(PERFORATIONS: Perforated? XYes No.	Cemented Gravel Blue	102 178	8 601
Type of perforator used Mills Knife		178 180	60'
1 2	Cemented Gravel Brown	180 254	241
7200 730 480		254 272	401
1000 perforations from 550 rt. to 990		272 304	40'
	Cemented Gravel Hard	304 308	3 40'
perforations from	Brown Clay & Gravel Med	308 478	3 50 '
perforations from	Sandy Clay & Gravel med	47 8 596	
perforations from ft. to ft.	Sticky Blue Clay	596 655	
(7) SCREENS: Well screen installed? Yes		655 702	301
Manufacturer's Name		702 716	
Type Model No		716 742	301
Diam. Slot size Set from ft. to ft.	Brown Clay Gravel black	= 1 = 5.	
Diam Slot size Set from ft. to ft.	l 	742 789	
(8) WATER LEVEL: Completed well.	Blue Clay Some gravel	789 1 00	0 0 11 '
Static level 47 ft. below land surface Date 5/7/68		-	
	To Be Deepened		
A sian pressure lbs. per square inch Date			
(9) WELL TESTS: Drawdown is amount water level is lowered below static leve Columbia			
Was a pump test made? X Yes No If yes, by whom? Pump	77.7.7.7.7.7.7.7.7.7.7.7.7.7.7.7.7.7.7.7	<u> </u>	
yind: 460 gal./min. with 144 ft. drawdown after hrs.	Work started 1/15/68 19 Complete		
500 . 193 . 10 .	Date well drilling machine moved off of well	5/9/68	19
. 618 . 228 . 20	Drilling Machine Operator's Certification:		
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my dir rials used and information reported abov	rect supervision	on. Mate-
Artesian flow g.p.m. Date	knowledge and belief.		
Temperature of water 53 Was a chemical analysis made? ☐ Yes 1 No	[Signed]	Date June 2	7., 19.68
(10) CONSTRUCTION:	·		
Well seal—Material used Grout	Drilling Machine Operator's License No	277	
Depth of seal 71 tt.	Water Well Contractor's Certification:	1,	
Diameter of well bore to bottom of seal24 in.	This well was drilled under my jurisdic		report is
Were any loose strata cemented off? Yes No Depth	true to the best of my knowledge and belief. NAME Stoffel Bros. Drilling Co.		
Was a drive shoe used? X Yes □ No	NAME STOIL EL Bros. Dril. (Person, firm or corporation)	(Type or pri	
Did any strata contain unusable water? 🗷 Yes 🗌 No	P+ 2 Boy 78 La Gr	ande, Or	
Type of water? Surface depth of strata 20'	Address Rt 2 DOX 10 DA GI	United 9 OI	OBOM.
Method of sealing strata off Surface Seal	Island Robert N Holle		
Was well gravel packed? ☐ Yes ♣ No Size of gravel:	[Signed] Robert V Staffer (Water Why Contract	tor)	
THE WELL BLAVEL PACKETS 1 169 110 SIZE OF BLAVEL		Aure 27	