

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WALL
279

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED

APR 20 1976

State Well No. 25/44E-3db
State Permit No. G-8610
WELL #1

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

(1) OWNER:

Name OREGON STATE FISH COMMISSION
Address 1400 SW 5th PORTLAND ORE

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
6" Diam. from 0 ft. to 86 ft. Gage 250
5" Diam. from 83 ft. to 288 ft. Gage 250

PERFORATIONS:

Perforated? Yes No.
Type of perforator used TARCH
Size of perforations 1/4 in. by 4 in.
400 perforations from 100 ft. to 288 ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: 18.3 gal./min. with 42 ft. drawdown after 10 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used BENONITE
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 6 sacks
Brand name of bentonite PRISM GEL
Number of pounds of bentonite per 100 gallons of water 70 lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELLS/PT.

County WALLOWA Driller's well number
Section 3 T. 25 R. 44E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 92 ft.
Static level 6 ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0
Depth drilled 288 ft. Depth of completed well 288 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	1	
BLACK CLAY	1	5	
FINE SAND + COARSE GRAVEL	5	64	
BROWN CLAY	64	75	
RED CLAY	75	86	
BLACK ROCK	86	92	
RED CLAY	92	105	6'
RED ROCK (SOFT)	105	140	
BROWN ROCK (SOFT)	140	160	WATER
BLACK ROCK WITH TRACES OF RED-BROWN			
*YELLOW ROCK	160	190	
RED ROCK (SOFT)	190	208	WATER
BLACK ROCK HARD	208	288	

Work started 2/28 1976 Completed 3/15 1976
Date well drilling machine moved off of well 3/15 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] _____ Date 3/15 1976
(Drilling Machine Operator)
Drilling Machine Operator's License No. 472

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name BOA DRILLING CO (Person, firm or corporation) (Type or print)
Address 101 Box 452 HARRIS
[Signed] _____ Date 3/15 1976
(Water Well Contractor)
Contractor's License No. 578 Date 3/15 1976