WATER WELL REPORT STATE OF OREGON



RECEIVED State Well No. 5N /43E-4ba

WATER	RESC	OURCES	State Permit No.	*************************
SALEM, OREGON		veri. I		

(1) OWNER:	(10) LOCATION OF WELL:		
Name Chris Lardner	County Wallowa Driller's well number 1478		
Address Troy Route, 85	NE 4 NW 4 Section 4 T. 5N R. 43E W.M.		
City Enterprise State Ore.	Tax Lot # Lot 19 Blk 4 Subdivision		
(2) TYPE OF WORK (check):	Address at well location: Same		
New Well			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
	Depth at which water was first found		
77	Static level 35 ft. below land surface, Date 6/22/82		
Rotary Air 🐧 Driven 🗆 Domestic 🛣 Industrial 🗆 Municipal 🗆 Rotary Mud 🗆 Dug 🔲 Irrigation 🗆 Test Well 🗆 Other 🖂	Artesian pressure lbs. per square inch. Date		
□ Bored □ Thermal: Withdrawal □ Reinjection □	(12) WELL LOG: Diameter of well below casing6. inches		
(5) CASING INSTALLED: Steel Plastic M	Depth drilled 142 ft. Depth of completed well 142 ft.		
(5) CASING INSTALLED: Steel M Plastic M Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show		
65/8 Diam from 2. A.G. 6 to29 ft. Gauge250	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level		
ft. Gauge	and indicate principal water-bearing strata.		
LINER INSTALLED:	MATERIAL From To SWL		
4"Diam.from 22ft.to 142.ft. Gauge 160 PSI	0.7		
(A) DEDUCE A PLONG	1		
(6) PERFORATIONS: Perforated? 【XYes ☐ No Type of perforator used Knife	Black basalt w/brown seams 2/, 68 35 Basalt w/green deposits (M.S.) 68 79		
Size of perforations $1/8$ in by 4 in.	Water at 45 feet		
perforations from 102 ft. to 142 ft.	Basalt (M.H.) 79 196 35		
perforations from	Water at 90 feet		
perforations from	Redish decomposed rock(S) 105 115		
	Black basalt (M.H.) 115 127		
(7) SCREENS: Well screen installed? ☐ Yes X☐ No Manufacturer's Name	Basalt w/green deposits 127 142 35'		
Type	Water area		
Diam. Slot Size Set from ft. to ft.			
Diam. Slot Size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered			
below static level			
Was a pump test made? ☐ Yes 🛣 No If yes, by whom?			
dd: gal/min. with ft. drawdown after hrs.			
Air test 28 gal./min. with drill stem at 140 ft. 1 hrs.			
Bailer test gal/min, with ft, drawdown after hrs.			
Artesian flow g.p.m. An enperature of water Depth artesian flow encountered ft			
O TO COLOR TO THE TAXABLE PARTY OF TAXABLE PARTY	Work started June 22 19 82 Completed June 22, 1982		
(9) CONSTRUCTION: Special standards: Yes □ No 🗓	Date well drilling machine moved off of well June 22 1982		
Well seal—Material used Cement grout	Drilling Machine Operator's Certification:		
Well sealed from land surface to 29 feet	This well was constructed under my direct supervision. Materials used		
Diameter of well bore to bottom of sealin.	and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal	[Signed] Oralling Machine Operator) Date		
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 1478		
from bottom up	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is true to		
Was pump installed? NO Type HP Depth ft.	the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Patrick R. Uhlenkott (Type or print)		
Oid any strata contain unusable water? Yes XNo	Address By 1, Box 35; Fenn, Idaho 83531		
Type of Water? Gect depth of strata	Think R 1100 Oct		
Method of sealing strata off	(Water Well Contractor)		
Was well gravel packed? ☐ Yes 🛣 No Size of gravel:	Contractor's License No. 1478DateAug. 3,, 19.82		
Gravel placed from			