

NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97301

within 30 days from the date
of well completion.

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No.

State Permit No.

(1) OWNER:

Name Warren B. Doney
Address Florida B. Enterprises Inc. 97828

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 130 ft. Gage 217
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after 3 hrs.

"By Air Meter - 15 gal per min."
" " " " " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water 57 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Drill mud

Well sealed from land surface to 126 ft.

Diameter of well bore to bottom of seal 9" in.

Diameter of well bore below seal 6" in.

Number of sacks of cement used in well seal 3 sacks

Number of sacks of bentonite used in well seal 126 or 130 sacks

Brand name of bentonite 126 or 130

Number of pounds of bentonite per 100 gallons of water 126 or 130

Was a drive shoe used? ☐ Yes ☒ No Plugs ☐ Size of plug ft.Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel: ft.

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Wallowa Driller's well number1/4 1/4 Section 5+8 T. 5 N R. 43 E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 127 ft.

Static level 109 ft. below land surface. Date 11/17/70

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 160 ft. Depth of completed well 160 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown soil	0	6	
Brown Clay & Boulder	6	60	
Brown Basalt	60	63	
Blue soft clay	63	124	
Brown Basalt	126	160	-109

Work started 11/4 19 70 Completed 11/17 19 70

Date well drilling machine moved off of well 11/17/ 19 70

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Richard W. Davis Date 11/18/ 19 70
(Drilling Machine Operator)

Drilling Machine Operator's License No. 147

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Richard W. Davis
(Person, firm or corporation) (Type or print)

Address P.O. Box 163 m-f, One 97862

[Signed] Richard W. Davis
(Water Well Contractor)

Contractor's License No. 159 Date 11/18/ 19 70