MAY 101976 State Well No. 1N/2E-11aa WATER WELL REP of this report are to be filed with the STATE OF OREGON TER RESOURCES DEPT. STATE ENGINEER, SALEM, OREGON 97310 (Please type or print) SALEM. OREGON'S Permit No. within 30 days from the date (Do not write above this line) იი2269 of well completion. (10) LOCATION OF WELL: (1) OWNER: Wasco Driller's well number County Albert R. Wasson 14 NE 14 Section 11 T. 1 N R. 12 Address Route 4, Box 57 The Dalles, Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New WellX Deepening \square Reconditioning \square Abandon \square If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): (3) TYPE OF WELL: Depth at which water was first found Rotary Static level 272 Domestic Industrial | Municipal | ft. below land surface. Date Cable Jetted ibs. per square inch. Date Irrigation Test Well | Other Artesian pressure CASING INSTALLED: Threaded | Welded (12) WELL LOG: Diameter of well below casing 8 "Diam. from 0 ft. to 156 ft. Gage 250 410 ft. Depth of completed well Depth drilled Formation: Describe color, texture, grain size and structure of materials; " Diam. from _____ft. to _____ft. Gage and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? | Yes | No. Type of perforator used MATERIAL 55 arge rocks & boulders in. by Size of perforations Sandstone, prown 55 85 ___ perforations from ____ ft. to ____ ft. 85 Sandstone, perforations from _____ft. to _____ft. few cuttings 95 Sandstone, brown perforations from Clay, light brown 1401 (7) SCREENS: Gravel, pea 145 Well screen installed? ☐ Yes ☐XNo Manufacturer's Name Clay, rocks Rocks, hard bonded Diam. Slot size Set from ft. to ft. 183 Clay, yellow Diam. Slot size set from ft. to ft. Bandstone, light brown 185 197 202 landstone, grey Drawdown is amount water level is lowered below static level (8) WELL TESTS: Bandstone, brown sandy 202 Sandstone, brown Was a pump test made?
Yes No If yes, by whom? Sandstone, grev Yield: gal./min. with ft. drawdown after hrs. Sandstone, brown 282 Sandstone, brey Sandstone, brown 150 gal./min. with 110 ft. drawdown after 7 Boller test 292 andstone, grey course andstone, grey fine g.p.m. perature of water 58 Depth artesian flow encounteredft. Work started March 15 19 76 Completed April Date well drilling machine moved off of well April 9 (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used Bentonite This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief, Diameter of well bore to bottom of seal in. (Drilling Machine Operator)

Date May 6, 19 76 Diameter of well bore below seal in. Drilling Machine Operator's License No. Number of sacks of bentonite used in well seal _______ sacks Brand name of bentonite Yellowstone Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is _____lbs./100 gals. true to the best of my knowledge and belief.

Gilbert Clayton Well Drilling Was a drive shoe used? XYes \(\subseteq \) No Plugs Size: location ft. Name (Person, firm or corporation) (Type or print)

Address Route 1, Box61-A, The Dalles, Ore Did any strata contain unusable water?

Yes

No Type of water? Method of sealing strata off (Water Well Contractor)

Contractor's License No. 569 Date May 6 Was well gravel packed?

Yes No Size of gravel:

TICE TO WATER WELL CONTRACTOR
The original and first copy

Albert R. Wasson Well Log dated May 6, 1976 Page 2

Sandstone,	Brown	332	342
Sandstone,		342	349
Sandstone,	-	349	399
Sandstone.	Grev	399	410

RECEIVED

MAY 1 0 1076

WAT IN DESOURCES DEPT, DALEM, CREGON