	7		
	Soregon 002355 State Well No. 1//1 State Permit No.	2-2	22 N
within 30 days from the date of well completion.	be or print) State Permit No		
(1) OWNER:	(11) WELL TESTS: Drawdown is amount w lowered below static lev	ater leve el	lís
Name Los Stewart	Was a pump test made? 🗌 Yes 🂾 No If yes, by whom		
Address T.O. Bax 761	Yield: gal./min. with ft. drawdown		hrs.
The Dalles, Oregon 97058	n n n		"
(2) LOCATION OF WELL:	<i>n n n</i>		"
	Bailer test 32 gal./min. with 0 ft. drawdow	vn after	hrs.
County Wasco Driller's well number	Artesian flow g.p.m. Date		
1/4 1/4 Section T. R. W.M.	Temperature of water 60 Was a chemical analysis made? 🗌 Yes 🙀 No		
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing 6 ^{tt} Depth drilled 180 ft. Depth of completed well 181 ft.		
	Formation: Describe by color, character, size of material and structure, and show thickness of aguifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.		
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	Boulders, large	0	5
New Well 🛣 Deepening 🗆 Reconditioning 🗆 Abandon 🗆	Sandstone, brown rocky	5	16
I indonment, describe material and procedure in Item 12.	Boulders, large	16	27
(1) PRODOSED LISE (check): (5) WVDE OF WELL.	Sandstone, grev rocky	27	52
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Sandstone, grey sandy	52	101
Domestic K Industrial Municipal Cable 4 Jetted	Water Bearing		
Irrigation Test Well Other Dug Bored	Sandstone, brown sandy	101	128
(6) CASING INSTALLED: Threaded	Water Bearing		
6 "Diam. from 0 ft. to $41\frac{1}{2}$ ft. Gage 250	Sandstone, grey porous rocky	128	146
	Water Bearing		
"Diam. from	Sandstone, brown rocky porou	8 146	169
	Water Bearing		······
(7) PERFORATIONS: Perforated? Yes No	Sandstone, grey	169	180
Type of perforator used	Water Bearing		+
Size of perforations in. by in.			مان دورنده میر <u>یک</u>
		•	<u> </u>
perforations from ft. to ft.			
			· · · · · ·
	- ·		
(8) SCREENS: Well screen installed? Yes X No	· · · · · · · · · · · · · · · · · · ·		
Manufacturer's Name			
Model No.			
Slot size Set from ft. to ft.	Work started July 14, 19 66 Completed Aug	. 1,	1966
Diam	Date well drilling machine moved off of well AUG.	-	1966
(9) CONSTRUCTION:	(13) PUMP:	<u>و</u>	1900
Well seal-Material used in seal	Manufacturer's Name		
Depth of seal ft. Was a packer used <u>Ves-sand</u>	Manufacturer's Name		
Diameter of well bore to bottom of sealin.	W		
Were any loose strata cemented off? 🗌 Yes 🕅 No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? \mathbf{X} Yes \Box No	This well was drilled under my jurisdiction a	and this	report is
Was well gravel packed? [] Yes [] No Size of gravel:	true to the best of my knowledge and belief.		- <u>-</u>
Gravel placed from ft. to ft.			
Did any strata contain unusable water? 🗍 Yes 🔽 No	NAME Bert Clayton and Son (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address2313 E. 10th St., The Dalles, Ore.		
Method of sealing strata off	Drilling Machine Operator's License No.	29	
(10) WATER LEVELS:	Bust Clayton		
Static level 49 ft. below land surface Date 8-1-66	(Water Well Contractor)		
Artesian pressure lbs. per square inch Date		<u>v </u>	, 19.00
USE ADDITIONAL S	HEETS IF NECESSARY)		

. .