5 TO 1			
NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be	WASC	2 = 1 - 4 1	· · · · · ·
	ELL REPORT	113-	.5 H
filed with the CGONTEENGINSTATE OF WITHIN 30 days from the date of well completion.	F OREGONU (2455) state Weil No. 42455 State Permit No. 42455	/	· · ·
(1) OWNER: Name J. J. Fleck	(11) WELL TESTS: Drawdown is amount lowered below static lo	water level	is
Address Route 4	Was a pump test made? A Yes □ No If yes, by whom? Ariller Yield 15 gal /min with 20 ft drawdown actor 1		
The Dalles, Oregon	vield 15 gel./min. with 20 ft. drawdown after 1 hrs.		
	······································		<u></u>
(2) LOCATION OF WELL: County Wasco Driller's well number	Bailer test gal./min. with ft. drawdown after hrs.		
SE 40N E4 Section 5 T. IN R. 13 E.W.M.	Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner	Temperature of wate 58° Was a chemical analysis	made? 🔲 Y	es Tr No
West applick B. Fryst land Park,	(12) WELL LOG: Diameter of well below casing 6"		
Columpia Creat add	_, Depth drilled 190 ft. Depth of completed well 191 ft.		
	Formation: Describe by color, character, size of materic show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each o	the materi hange of	al in each formation.
(1) MUDE OF WORK (-LL).	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	Soil, brown	0	1
w Well X Deepening Abandon Abandon Abandon Abandon Abandon Abandon Abandon Well X	Sandstone, brown		3.
	Sandstone, rocky, light brow		14
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Sandstone, brown w/boulders Boulders, large	$\frac{14}{16}$	<u>16</u> 20
Cable X Jetted	Sandstone, grey w/boulders	20	23
Irrigation Test Well Other Dug Bored	Sandstone, brown, sandy	23	48
(6) CASING INSTALLED: Threaded [] Welded []	Sandstone, grey, sandy	48	56
6." Diam. from 0 ft. to 141 ft. Gage . 250	Clay, light brown	56	67
"Diam. from ft. to ft. Gage	Sandstone, grey, rocky	67	78
"Diam. from ft. to ft. Gage	<u>Clay, white</u> Sandstone, grey	78	79
(7) PERFORATIONS: Perforated? [] Yes X No	Clay, brown	110	110 120
Type of perforator used	Sandstone, grey	120	127
Size of perforations in. by in.	Sandstone, light brown	127	189
ft, to ft,	Sandstone, brown, sandy	139	144
perforations from ft. to ft.	Sandstone, pourous, rocky	144	160
perforations from ft. to ft. to ft. to ft.	Sandstone, light brown, porous		166
perforations from ft. to ft.	Sandstone, brown, sandy Sandstone, brown, porous	166 176	<u>176</u> 185
	Sandstone, brown, sandy	185	190
(8) SCREENS: Well screen installed? Yes X No Manufacturer's Name			
	Water bearing from 155'		· · · · · · · · · · · · · · · · · · ·
more Model No ft. to ft.			
Diam Slot size Set from ft. to ft.	Work started April 21,19 66 Completed M	ay 12,	19 66
	Date well drilling machine moved off of well May	12,	<u>19 66</u>
(9) CONSTRUCTION:	(13) PUMP:		
Well seal-Material used in seal Bentonite	Manufacturer's Name Fairbanks Morse		
Depth of seal <u>20</u> Diameter of well bore to bottom of seal <u>10</u> in	Type: Submersible		
	Watan Wall Contractors of stiffs in		
Were any loose strata cemented off? \Box Yes \mathbf{X} No Depth	Water Well Contractor's Certification:		
Was well gravel packed? \Box Yes X No Size of gravel:	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	and this r	report is
Gravel placed from ft. to ft.			
Did any strata contain unusable water? 🔲 Yes 🔀 No	NAME Bert Clayton and Son (Person, firm or corporation) (Type or print) Address 2313 E. 10th St., The Dalles, Ore.		
Type of water? Depth of strata	Address 2313 E. 10th St., The I	Dalles	, Ore.
Method of sealing strata off	Drilling Machine Operation 100		
(10) WATER LEVELS:	Drilling Machine Operator's License No. <u>129</u>		
	I I A A A I I WATAL TAM		
	[Signed] Ser Claybon		
Static level 126 ft. below land surface Dat5-12-66 Artesian pressure Ibs. per square inch Date	[Signed]		₁₉ 66