NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

REGEIVED WASC WATER WELL REPORT SEP 2 19 Figure Well No. ..

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON

97310

(Please type or print) ATER RESOURCEState Permit No. /W/138-6960

002474

(Do not write above this line) SALEM, CRECON

(1) OWNER:	(10) LOCATION OF WELL:
Name Claude W. Smith	County Wasco Driller's well number
Address Rt.4 36-D	NE 1/4 NE 1/4 Section 6 T. 1N R. 13E W.M.
The Dalles, Oregon	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	235
Rotary Driven Domestic X Industrial Municipal	Depart at which water was first found
Cable Jetted	Static level 162 ft. below land surface. Date 1 Aug
Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded Welded	(12) WELL LOG: Diameter of well below casing 6
6 CASING INSTALLED: Threaded T	260
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
DEDUCE A DIONG.	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes You	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Gravel 160 165
perforations fromft. toft.	Sandstone tan 165 184
perforations from ft. to ft.	Claystone gray WB 184 360 162
perforations fromft. toft.	
(7) SCREENS: Well screen installed? ☐ Yes ★1 No	
Manufacturer's Name	
Type Model No.	
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(O) TIVELY DESCRIPTION OF THE PROPERTY OF THE	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes X☐ No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
12 gal. min. air test " "	
" " " "	
gal./min. with ft. drawdown after hrs.	
A A A A A A A A A A A A A A A A A A A	
an flow g.p.m.	76
perature of water Depth artesian flow encounteredft.	Work started 1 Aug 1976 Completed 1 Aug 1976
(9) CONSTRUCTION:	Date well drilling machine moved off of well 1 August 19 76
Well seal—Material used Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface to 18 ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	
Number of sacks of cement used in well seal O sacks	(Drilling/Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 737
Brand name of bentonite <u>International</u>	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	
Did any strata contain unusable water? ☐ Yes ☐ No	Name Richard J. Murray (Type or print)
Type of water? depth of strata	Address 3712 W 8th The Dalles, Oregon
Method of sealing strata off	some Pike A 7
Was well gravel packed? ☐ Yes ⊠ No Size of gravel:	[Signed] Cuchiand J. M. Marian) (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 606 Date 21 August 19.76
10. 00	Contractor o License No