



File Original, and Duplicate with the STATE ENGINEER, SALEM, OREGON

WATCH WELL DRILLERS REPORT  
WASC 2684  
STATE OF OREGON

Do Not State Well No. 113-36  
Fill In State Permit No. G263

(1) OWNER: S.A. SKIRVING  
Name by Dr. John H. Skirving  
Address 909 W 9th Street  
The Dalles, Oregon

(10) WELL TESTS: OBSERVATION WELL  
Was a pump test made?  Yes  No If yes, by whom?  
Yield: gal./min. with ft. draw down after  
Artesian flow 1500 g.p.m.  
Shut-in pressure 128 lbs. per square inch.  
Baller test g.p.m. with ft. drawd  
Temperature of water 78 Was a chemical analysis made?  Yes   
Was electric log made of well?  Yes  No

(2) LOCATION OF WELL:  
County Wasco Owner's number, if any - # 6233  
R. F. D. or Street No. Upper 2 Mile  
Bearing and distance from section or subdivision corner  
The Dalles Ore = 2862' S + 43' E from NW cor Sec. 32

(11) WELL LOG:  
Diameter of well, 8 inches.  
Total depth 805 ft. Depth of completed well 805  
Formation: Describe by color, character, size of material and structure, show thickness of aquifers and the kind and nature of the material in stratum penetrated, with at least one entry for each change of forma:

(3) TYPE OF WORK (check):  
New well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 11.

(4) PROPOSED USE (check):  
Domestic  Industrial  Municipal   
Irrigation  Test Well  Other   
(5) EQUIPMENT:  
Rotary   
Cable   
Dug Well

(6) CASING INSTALLED:  
Threaded  Welded   
FROM 0 ft. to 265 ft. 8" Diam. Standard Line Pipe  
Type and size of shoe or well ring  
Describe joint Cemented from bottom to surface

0 ft. to	28 ft.	Gravel and boulders.
28 "	158 "	Brown sandstone, varying to
158 "	177 "	Brown clay and sand.
177 "	260 "	Brown sandstone.
"	"	Dalles formation above
260 "	269 "	Brown lava, Hard.
269 "	278 "	Gray lava, coarse texture.
278 "	298 "	Brown lava, fine texture.
298 "	318 "	Brown sandstone, streaks cl
318 "	325 "	Gray lava, coarse texture.
325 "	368 "	Blue lava.
368 "	390 "	Black lava, blue caly seams
390 "	400 "	Brown lava, green clay seam
400 "	412 "	Brown clay and rock.
412 "	468 "	Hard blue basalt.
468 "	594 "	Black basalt. Artesian flow
"	"	at 471. 471 to 550 flow in
"	"	creased to around 100 GPM.
594 "	802 "	Hard gray basalt.
802 "	805 "	Black, fractured basalt. B
"	"	flow water.

(7) PERFORATIONS:  
Type of perforator used  
No. of perforations in., length. by in.  
FROM ft. to ft. perf per foot No. of rows

SCREENS:  
Give Manufacturer's Name, Model No. and Size

(8) CONSTRUCTION:  
Was a surface sanitary seal provided?  Yes  No To what depth ft.  
Were any strata sealed against pollution?  Yes  No  
If yes, note depth of strata  
FROM ft. to ft.  
METHOD OF SEALING

(9) WATER LEVELS:  
Depth at which water was first found ft.  
Standing level before perforating ft.  
Standing level after perforating ft.  
Log Accepted by:

[Signed] S.A. SKIRVING & SON Dated 2-13, 1957  
John H. Skirving

Ground elevation at well site 1002 feet above mean sea l  
Work started July 10, 19 56 Completed Nov. 31, 19

Well Driller's Statement:  
This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief.

NAME Dorin Wilburn (Person, firm, or corporation) (Typed or printed)  
Address 812 E 7th Street, The Dalles, Oreg  
Driller's well number  
[Signed] Dorin Wilburn (Well Driller)  
License No. 80 Dated Jan. 7 19