NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT
STATE OF OREGONMAY 2 8 1975

State Well No. 10/14E-26

STATE	ENGINEER,	SALEM,	OŘEGO
	within 30 da	ys from t	he ďate
		completic	

STATE OF OREGONIAL A OIL	
STATE OF OREGONNAL & O IS	NEER State Permit No. 6-6584
RECE DVo Evrile above this SALEM, ORE	GON

1) OWNER: SEP - 2 1975	(10) LOCATION OF WELL:
	County Wasco Driller's well number
WAIER RESOURCES DEL	Se 34 SW 14 Section 26 T. ER. 14E W.M.
The Dalles, Oregon	Bearing and distance from section or subdivision corner
2) TYPE OF WORK (check):	
New Well ☐ Deepening ☒ Reconditioning ☒ Abandon ☐	
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
X- Post-one II	Static level 260 ft. below land surface. Date 17May75
Cable Jetted	
Oug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded X	(12) WELL LOG: Diameter of well below casing 8 & 6
7" Diam. from0 ft. to _3.00 ft. Gage _10	Depth drilled 417 ft. Depth of completed well 417 ft.
ft. Gageft.	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated,
PADAGO A TIONG	position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated? Tyes No.	
Type of perforator used Tourch	***************************************
Size of perforations 3/8 in. by 10 in.	CCean out and instal liner in drilled
60 perforations from 260 ft. to 299 ft.	by Pat Geelan which caved in
perforations from ft. to ft.	7, 12, 1, 1, 1, 2, 2, 2, 2, 2, 7
perforations from ft. to ft.	Basalt black visicular 360 367 Claystone vellow 367 370
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	
Manufacturer's Name	
Type Model No.	Basalt gray med. 382 395 Basalt brown 395 398
Diam. Slot size Set from ft. to ft.	Basalt gray 398 412
Diam. Slot size Set from ft. to ft.	Basalt black 412 417 260
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ⋊ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	
" Will be test pumped in "a few days"	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	Work started 16 May 1975 Completed 17 May 1975
pperature of water Depth artesian flow encountered ft.	Work started 16 May 1975 Completed 17 May 1975 Date well drilling machine moved off of well 18 May 1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well 10 Flay 13 75
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief
Diameter of well bore below sealin.	[Signed] Richard Musicap Date 22 May, 1975
Number of sacks of cement used in well seal sacks	Orilling Machine Operator's License No. 737
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's Precise 1101
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Richard J. Murray (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes No	Address 3712 W. 8th The Dalles, Oregon
Type of water? depth of strata	Address
Method of sealing strata off	[Signed] (Kichard) Mirrory
Was well gravel packed? Yes No Size of gravel:	(Water Well contractor)
Gravel placed from ft. to ft.	Contractor's License No. 606 Date 22 May , 1975
CICE ADDITIONAL C	HEETS IE NECESSARV) SP*45656-119