

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print) WATER RESOURCES DEPT
(Do not write above this line) SALEM, OREGON

RECEIVED

NOV - 4 1977

State Well No.

State Permit No.

1N/14E-26CC
6-7258

(1) OWNER:

Name George Harth
Address Rt 3, Box 37
The Dalles, OR 97058

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

None
Threaded Welded

" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Air
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

Temperature of water 62° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Old seal cement
Well sealed from land surface to 80 ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Wasco Driller's well number
SW 1/4 SW 1/4 Section 26 T. 1 N. R. 14 E. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 514 ft.
Static level 410 ft. below land surface. Date 10-25-77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 239 ft. Depth of completed well 656 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Rock, grey hard	417	514	
Rock, porous grey/opal	514	524	410
Lignite, black	524	526	"
Clay, green	526	530	"
Rock, porous grey	530	535	"
Rock, grey	535	540	"
Rock, porous black	540	560	"
Rock, grey	560	570	"
Rock, black porous	570	605	"
Rock, black	605	615	"
Rock, porous black	615	656	"

Work started Oct. 18 19 77 Completed Oct. 25 19 77

Date well drilling machine moved off of well Oct. 25 19 77

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Gilbert Clayton Date 10-28-77, 19.....
(Drilling Machine Operator)

Drilling Machine Operator's License No. 129

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Gilbert Clayton Well Drilling
(Person, firm or corporation) (Type or print)
Address Rt 1, Box 61-A, The Dalles, OR 97058

[Signed] Gilbert Clayton
(Water Well Contractor)

Contractor's License No. 569 Date Oct. 28, 19 77