NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

STATE OF OREGON JUNI 8 1975 State Well No. 2 N/11 E - 2 ac STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. (Blease type or print)STATE ENGINEER State Permit No. (Do not write above this linklem, OREGON

1) OWNER:	(10) LOCATION OF WELL:	
The state of the s	County Wasco Driller's well number	
Name Mosier Mobile Manor	NE 14 SW 14 Section 2 T. 2 R. 11E	W.M.
Address Mosier, Oregon	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 42	ft.
(0) 1111	Static level 72 ft. below land surface. Date 1	3 June
Schle D Jetted D		
Dug	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing	8
8 " Diam. from	Depth drilled 175 ft. Depth of completed well 17	5 ft.
ft. Gage	Formation: Describe color texture, grain size and structure of	materials;
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquiler	penetrateu,
	with at least one entry for each change of formation. Report eac position of Static Water Level and indicate principal water-bea	ring strata.
PERFORATIONS: Perforated? Tyes Yes No.		SWL
Type of perforator used	WATERIAL	
Size of perforations in. by in.	Rock broken 0 75	
perforations from ft. to ft.	Cray can	
perforations from ft. to ft.	Clay green	
perforations from ft. to ft.	Dagase gray we	
(7) SCREENS: Well screen installed? ☐ Yes 전 No	Claystone green WB 160 163 Basalt gray WB 163 175	
• •	Basarc gray WD	
Manufacturer's Name		
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		 -
" "	0 · · · · · · · · · · · · · · · · · · ·	
n n n n	TE TE	
Dunies tool Target Street Target Street		
Artesian flow g.p.m.	Work started 11 June 1975 Completed 13 June	ne 1975
perature of water Depth artesian flow encountered ft.	4.0	
(9) CONSTRUCTION:	Date wen drining internation	
Bentonite	Drilling Machine Operator's Certification:	norwician
Well seal—Material used 23 ft.	This well was constructed under my direct sur Materials used and information reported above are	true to my
Diameter of well bore to bottom of seal 12 in.	hest knowledge and beliefs	
Diameter of well bore below seal	[Signed] Dickory Date	<u>oui, F9/5.</u>
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 737	
Number of sacks of bentonite used in well seal sacks	Drining Wachine Operator 5 220000	
Brand name of bentonite Yellowstone	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and th	is report is
of water lbs./100 gals.	true to the best of my knowledge and belief.	
Was a drive shoe used? Yes □ No Plugs Size: location ft.	Name Richard J. Murray (Person, firm or corporation) (Type or	r print)
Did any strata contain unusable water? Yes 1 No	3712 W 8th The Dalles, Or	
Type of water? depth of strata	Address	
Method of sealing strata off	[Signed] Qualitated (Water Well Confractor)	
Was well gravel packed? Yes No Size of gravel:	(Water Well Confractor) 606 Porto 17 June	71
Gravel placed from ft. to ft.	Contractor's License No. 606 Date 17 June	, 19