NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

WASOVATER WELL REPORTE CEIVED

filed with the STATE ENGINEER, SALEM, OREGON 97310 STATE OF OREGON

JAN 30 1976 tate Well No.

within 30 days from the date of well completion. (Please special part within 30 days from the date)	ve this VALER RESOURCES TO EPT: NO SALEM. OREGON	o	***************************************
(1) OWNED.	(10) LOCATION OF WELL:		
(1) OWNER:	County Wasco Driller's well number #3		
Name Ron Guillory	SW 1/4 NE 1/4 Section 11 T. 2N R. 11E W.M.		
Address Rt.1 Box 950 Bend, Oregon	/4 /4 20000-		VV .1VI.
	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):			
New Well 🖔 Deepening 🗌 Reconditioning 🗍 Abandon 🗍			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 65	*	ft.
Cable Jetted Domestic Industrial Manicipal			
Dug	Artesian pressure lbs. per squar	e inch. Date	
CACING INSTALLED:	(40) TIPLE TOO		c
CASING INSTALLED: Threaded Welded \(\)	(12) WELL LOG: Diameter of well b		
6 "Diam. from 0 ft. to 55 ft. Gage • 250	Depth drilled 231 ft. Depth of completed well 231 ft.		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size	and structure of m	aterials;
ft. toft. Gage	and show thickness and nature of each stratus with at least one entry for each change of format	m and aquifer per	ietrated,
PERFORATIONS.	position of Static Water Level and indicate prin	icipal water-bearin	g strata.
PERFORATIONS: Perforated? Yes No.		1	SWL
Type of perforator used	MATERIAL	From To 3	SWL
Size of perforations in. by in.	Soil	l	
perforations from	Claystone & gravel		
perforations from ft. to ft.	Basalt gray	49 60	
perforations from ft. to ft.	Basalt brown WB	60 70	
perforations from	Basalt gray	70 205	
(7) SCREENS: Well screen installed? ☐ Yes ☐XNo	Basalt brown	205 220	
Manufacturer's Name	Basalt black WB	220 230	
Type Model No.	Claystone gray	230 231	165
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes X☐ No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.	<u> </u>		
15-GPM with 100% drawdown Air test "			
n n n			
Bailer test gal./min. with ft. drawdown after hrs.			
		1	
Artesian flow g.p.m.	Work started 15 Jan 176 Complete	16 Jan	₁₉ 76
perature of water Depth artesian flow encountered ft.			
(9) CONSTRUCTION:	Date well drilling machine moved off of well	16 Jan	1976
• •	Drilling Machine Operator's Certification	:	
Well seal—Material usedBentonite	This well was constructed under my	direct super	vision.
Well sealed from land surface toft.	Materials used and information reported best knowledge and belief.	above are true	to my
Diameter of well bore to bottom of seal		Date 28 Jan	0 10 76
Diameter of well bore below seal in.	(Drilling Machine Operator)		.; 19
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	8,28	
Number of sacks of bentonite used in well seal sacks Brand name of bentonite International	Diming Institute of		,
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisc	diction and this	report is
of waterlbs./100 gals.	true to the best of my knowledge and be	elief.	_
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	Name Richard J. Murray		
Did any strata contain unusable water? 🗌 Yes 灯 No	Name Richard J. Murray. (Person, firm or corporation)		
Type of water? depth of strata	Address 3712 W 8th The Dall	es, Urego	<u>[]</u>
Method of sealing strata off	Retall me	u1	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed]	kractor)	
	1 (/ //		₁₉ 76
Gravel placed from ft. to ft.	Olitacioi b Licelibe 140, Landiani. Date in		,