

RECEIVED

STATE OF OREGON

APR 30 1985

WATER WELL REPORT

(as required by ORS 537.660) WATER RESOURCES DEPT. PLEASE TYPE or PRINT IN INK

002780

24/12E-210

(for official use only)

(1) OWNER:

Name State of Oregon Parks Div.
Address State Transportation Bldg.
City Salem Ore 97310 State

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Air [] Driven [] Domestic [X] Industrial [] Municipal []
Rotary Mud [] Dug [] Irrigation [] Thermal: [] Withdrawal [] Reinjection []
Other: [] Piezometric [] Grounding [] Test []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal []
Thermal: [] Withdrawal [] Reinjection []
Other: [] Piezometric [] Grounding [] Test []

(5) CASING INSTALLED:

Steel Threaded [X] Plastic Welded [X]
6" Diam. from 1 ft. to 130 ft. Gauge 250

LINER INSTALLED:

Steel Threaded [] Plastic Welded []

(6) PERFORATIONS:

Perforated? [X] Yes [] No
Size of perforations 1/4 in. by 3 in.
24 perforations from 75 ft. to 84 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [X] Yes [] No If yes, by whom? DRILLER
Flow: 75 gal./min. with 2 ft. drawdown after 8 hrs.

(9) CONSTRUCTION:

Special standards: Yes [] No [X]
Well seal—Material used CEMENT
Well sealed from land surface to 45 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 6 in.
Amount of sealing material 32 sacks [X] pounds []
How was cement grout placed? PUMPED

Was pump installed? NO Type HP Depth ft.
Was a drive shoe used? [X] Yes [] No Plugs YES Size: location 119 ft.
Did any strata contain unusable water? [] Yes [X] No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL by legal description:

County WASC SW 1/4 SW 1/4 of Section 2
Township 2N Range 12E WM.
MAYER-STATE PARK DALLS, ORE.

(11) WATER LEVEL of COMPLETED WELL:

Depth at which water was first found 25 ft.
Static level 16 ft. below land surface. Date 11-12-84
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 156 ft. Depth of completed well 119 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include CLAY-BOLDERS, BROKEN-LAVA, BLACK-SHALE, LAVA-ROCK.

Date work started 10-9-84 / completed 11-27-84
Date well drilling machine moved off of well 11-27 1984

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Harry May Date 11-28, 1984

(bonded) Water Well Constructor Certification:

Bond 505170 Issued by: WESTERN
On behalf of HARRY MAY

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief:

[Signed] Harry May
(Dated) 11-28-84

NOTICE TO WATER WELL CONSTRUCTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

SP*46866-690