

The original and first copy of this report are to be filed with the

STATE OF OREGON WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED NOV 1 1976 State Well No. 2N/12E-3cb State Permit No.

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

002794

WATER RESOURCES DEPT.

(1) OWNER:

Name Karl Johnson Address PO Box 481 Mosier, Oregon 97040

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

6" Diam. from 0 ft. to 18 ft. Gage .250

PERFORATIONS:

Type of perforator used Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [X] No Yield: 6 Gal. Min. air test 100% drawdown Bailer test Artesian flow Temperature of water

(9) CONSTRUCTION:

Well seal—Material used Bentonite Well sealed from land surface to 18 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 0 Number of sacks of bentonite used in well seal 1 Brand name of bentonite International Number of pounds of bentonite per 100 gallons of water 100 Was a drive shoe used? [X] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Wasco Driller's well number NW 1/4 SW 1/4 Section 3 T. 2N R. 12E W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 620 ft. Static level 342 ft. below land surface. Date 10 Oct Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6 Depth drilled 640 ft. Depth of completed well 640 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Soil, Basalt blue hard, Rock brown soft, Basalt gray hard, Rock brown wet soft, Basalt black damp, Basalt gray hard, Basalt black damp, Basalt gray hard, Basalt black damp, Basalt gray hard, Basalt black visic., Basalt gray hard, Black visic. WB.

Work started 7 Oct 19 76 Completed 10 Oct 19 76 Date well drilling machine moved off of well 10 Oct 19 76

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Richard J. Murray Date 14 Oct 19 76 Drilling Machine Operator's License No. 737

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Richard J. Murray Address 3712 W 8th The Dalles, Oregon [Signed] Richard J. Murray Contractor's License No. 606 Date 14 Oct 19 76