NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

WATER WELL REPORT

State Well No.	2N	ME	-6
State Well No.	7		

STATE ENGINEER, SALEM, ORE IN 5730 [] (Please type or print) within 30 days from the date of well completion. OCT 1 3 1975

(Do not write above this line)

	14	P.C
00	18	35

State	Well No	o. 🦾	 / <u>.</u>	<i></i>	\Box	
State	Permit	No.	 			-5-7

(1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:	
Name Clarence D. Byrgalem, OREGON	County Wasco Driller's well nur	nber
Address POBox 166 Mosier, Oregon	SE 1/4 SW 1/4 Section 6 T. 2N	R. 12E W.M.
Address POBOX 1.00 Tivo LC1	Bearing and distance from section or subdivision	n corner
(2) TYPE OF WORK (check):		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	T-N-1	*
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	<u>.</u> 11.
	• •	f+
(3) TYPE OF WELL: (4) PROPOSED USE (check):		128
Rotary 🔯 Driven 🗆 Domestic 💆 Industrial 🗆 Municipal 🗆	Static level 42 ft. below land su	
Cable	Artesian pressure lbs. per square	inch. Date
CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well be	elow casing8
8 " Diam. from 0 ft. to 174 ft. Gage • 250	Depth drilled 275 ft. Depth of comple	
ft. Gage	Formation: Describe color, texture, grain size a	
" Diam. from ft. to ft. Gage	and shows thickness and nature of each stratum	o and adulier peneirated,
	with at least one entry for each change of format position of Static Water Level and indicate princ	ion. Report each change in
PERFORATIONS: Perforated? Yes X No.	position of Static Water Level and manager principles	
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Soil	0 18
perforations from ft. to ft.	Clay yellow	18 30
perforations fromft. toft.	Clay brown	30 40
perforations from ft, to ft.	Clay red brown	40 65
periorations from	Gravel med.	65 70
(7) SCREENS: Well screen installed? Yes X No	Clay brown	70 80
Manufacturer's Name	Clay white	80 120
Type Model No	Clay brown	120 128
Diam Slot size Set from ft. to ft.	Gravel med WB	128 175
Diam. Slot size Set from ft. to ft.	Clay white	175 210 210 241
(8) WELL TESTS. Drawdown is amount water level is	Gravel small WB	241 255
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Clay white	255 275 42
Was a pump test made? ☐ Yes ☐ KNo If yes, by whom?	Gravel med WB	233 213 42
Viold: gal/min, with ft. drawdown after hrs.		
00 gal min with 100% dra,wdown "		
" Air test" " "	The second secon	
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Work started 6 Oct 1975 Complet	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	9 Oct 1975
• •	Drilling Machine Operator's Certification	:
Well seal-Material used Bentonite	This well was constructed under my Materials used and information reported	direct supervision.
Well sealed from land surface to18ft.	I Dest Knowledsevally believe //	
Diameter of well bore to bottom of seal	[Signed] (Drilling Machine Operator)	Date 9 Oct., 1975.
Diameter of Men porc perov pear	(Drilling Machine Operator)	010
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.	O.QQ.
Number of sacks of bentonite used in well sealsacks	\	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	listion and this report is
of water	This well was drilled under my jurisd true to the best of my knowledge and be	lief.
Was a drive shoe used? ♀ Yes ☐ No Plugs Size: location ft.		
Did any strata contain unusable water? Yes No	Name Richard J. Murray	
Type of water? depth of strata	Address 3.712 W 8th The Dal	les, Oregon
Method of sealing strata off	[Signed] Richard Muss	iaij
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Con	tracton.
Gravel placed from ft. to ft.	Contractor's License No. 6.06. Date S)_Oct, 197.5_