STATE OF OREGON

WATER RESOURCESSIPERFE OF PRINT IN INK

SALEM, OREGON

SALEM, OREGON

2n	112E-	7 db
-		72

WATER WELL REPORT (as required by ORS 537.765)

					•••••	
(for	offi	cial	use	only)

Shield, Mills	ALCO TO CAMPAON OF THE Land	descriptions
1) OWNER:	(10) LOCATION OF WELL by legal	description.
Name Diego Leon 009855	County Wasco NE 1/4 NE 1/4 o	4 077
Address 1275 Dry Creek Rd. \ 002033	Township 2N (Township is North or South), Range (12E ,, WM.
City Mosier, State Oregon	Tex Lot Lot Block Subdivision	
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address) MOS	sier, Or.
_		
New Well Me Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 12.		
	(11) WATER LEVEL of COMPLET	ED WELL:
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 144	ft.
Rotary Air 42 Driven Domestic Thormal	Depth at which water was miss to account	land surface. Date 4-28-8
Rotary Mud Dug Irrigation X Withdrawal Reinjection		square inch. Date
Other: Bored		7 casing 8"
	(12) WELL LOG: Diameter of well below fit. Depth of	casing
(5) CASING INSTALLED: Steel 🛣 Plastic 🗆 - Threaded 🗆 Welded	Etion Describe color texture grain size and structure	of materials; and show thickness
8	and nature of each stratum and aquifer nenetrated, with at I	east one entry for each change of
Diam. from tt. to Gauge	formation. Report each change in position of Static Wat water-bearing strata.	er Level and indicate principal
	water-nearing strata.	
LINER INSTALLED: Steel Plastic Threaded Welded	MATERIAL	From To SWL
"Diam. fromft. toft. Gauge	Clay	0 3
	Sandstone coarse	3 14
(6) PERFORATIONS: Perforated? Yes No	Basalt med blk	14 26
Size of perforations	Basalt hard blk	26 47
perforations from ft. to ft.	Basalt hard gray	47 65
perforations from	Basalt med-hard bray	65 82
perforations from ft. to ft.	Basalt hard gray	82 144
(7) SCREENS: Well screen installed? Yes No	Basalt broken bak W/B	144 149 82
Manufacturer's Name		
Type		
Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size Set from ft. to ft.	- -	
Drawdown is amount water level is lowered		
(8) WELL TESTS: below static level		
Was a pump test made? ☐ Yes ☐ No If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.		
u u u		
Air test 1.50 gal./min. with drill stem at 1.40 ft. 1 hrs.		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Date work started 4-26-85 /complet	ted 4-29-85
	Date work started	29-85 19
(9) CONSTRUCTION: Special standards: Yes □ No X Well seal—Material usedCement	Date wen a ming machine	
Well seal—Material used	(unbonded) Water Well Constructor Certific	ation (if applicable):
Well sealed from land surface to	This well was constructed under my direct su	pervision. Materials used and
Diameter of well bore to bottom of sealin.	information reported above are true to my best kr	
0	[Signed]	Date, 19
Amount of sealing material sacks be pounds U How was cement grout placed? Grout pump	(handad) Water Well Constructor Certificat	ion:
	Bond 961 560 5 Issued by: Kargl	, Elwwod & Geigt
	(number) (O	urety Company Mame)
Was pump installed? NO Type IIP Depth ft.	On behalf of Marinelli & Austin	n Drilling Co.
Was a drive shoe used?	(type of print name of v	
Was a drive shoe used?	This well was drilled under my jurisdiction	and this report is true to the
Type of Water? depth of strata	best of my knowledger and being f:	
Type of masses	(Signed) To Marke Clubb	***************************************
Method of sealing strata off Was well gravel packed? ☐ Yes	(Water Well Constru	ctor)
Was well gravel packed?	(Dated) 5-6-85	
NOTICE TO WATER WELL CONSTRUCTOR	WATER RESOURCES DEPARTMENT,	SP*46866-690
METER WATER WELL CONSTRUCTOR	11 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	