NOTICE TO WATER WELL CONTRACTOR
The Original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

Gravel placed from

WATER WELL REPORT.

STATE OF OREGON

(Please type or print)

State Well No. O.

State Well No. $\frac{2N}{2E}$

(Do not write above this line)

· · · · · · · · · · · · · · · · · · ·				
(1) OWNER:	(10) LOCATION OF WELL:			
Name THE KIR, Keeves	County Uance Driller's well number			
Address RT 1 Box 70	NE 1/2 1/2 1/4 Section 7 T. 2N R. 12 E W.M.			
maxice Mic 97040	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	50 Nand 250 E from SW Corner			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 405 ft.			
Rotary Driven Domestic Industrial Municipal Cable Jetted Domestic Municipal Domestic	Static level 2.55 ft. below land	surface.	Date /2	2/16/7
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squa	re inch.	Date	
(5) CASING INSTALLED: Threaded Welded				
9	(12) WELL LOG: Diameter of well below casing			
	Depth drilled 425 ft. Depth of completed well 425 ft.			
"Diam from ft. to ft. Gage ft. to ft. Gage ft. to ft. Gage	Formation: Describe color, texture, grain size	and struc	ture of n	naterials;
To the state of th	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
PERFORATIONS: Perforated? Yes Wino.	position of Static Water Level and indicate pri	ncipal wa	ter-bearii	ıg strata.
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	Top Soil Light Brown	0	2_	
perforations from ft. to ft.				
perforations from ft. to ft.	SAND Stone Light Brown	2.	240	-
perforations from ft. to ft.	Olasia	- 75	n: b	
(7) SCREENS: Well screen installed? Yes P No	CHUSTONE LIGHT Gray	240	260	
Manufacturer's Name	SANDSTON Light Grain	2.60	280	 :,
Type Model No.	SPRODEST CARE TO THE COLUMN	2.07	200	
Diam Slot size Set from ft. to ft.	RASALT BLACK Fractured	280	290	***
Diam Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BASACT BIACK HARD	290	40:5	
Was a pump test made? ☐ Yes ☐ No If yes, by whom? Drill(r-	BASALT POROUS LUB:	405	425	Z55
Yield: .257) gal./min. with 425 ft. drawdown after hrs.	- DECEMEN			
an n	REGEIVEU			
<i>"</i> " " " "	DEC 20 1979	 		
Bailer test gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT			
Artesian flow g.p.m.	SALEM OREGON			
mperature of water Depth artesian flow encountered ft.	Work started ()(122 19 1 Complete	ed (Y	可 31	19 7°1
(9) CONSTRUCTION:	Date well drilling machine moved off of well NOV 22 1976			
Well seal-Material used Coment grant	Drilling Machine Operator's Certification:			
Well sealed from land surface to 40 0	This well was constructed under my direct supervision.			
Diameter of well bore to bottom of seal 17/2 in.	Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore below seal	[Signed] (12) Schland Date 12/2, 1979			
Number of sacks of cement used in well seal 3hyds = 85 sacks	(Drilling Machine Operator)	137	ર્	-
How was cement grout placed?	Drilling Machine Operator's License No.			
2	Water Well Contractor's Certification:			
The state of the s	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address RT 4 BCX 34	3 7h	IE D	ALLES
Method of sealing strata off		21	1 (
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)			
	1	<i>~</i> ~ /	-4	

Contractor's License No.