

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WASCO WATER WELL REPORT

RECEIVED

ab

STATE ENGINEER, SALEM, OREGON 97210
within 30 days from the date
of well completion.

002868

STATE OF OREGON STATE ENGINEER
(Please type or print)
SALEM, OREGON
(Do not write above this line)

State Well No. 2N/12E-7
State Permit No. G-7678

(1) OWNER:

Name CLYDE ROOT
Address PO BOX 251 MOASIER, OREGON 97040

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded

" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 59° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County WASCO Driller's well number
NW 1/4 NE 1/4 Section 7 T. 2N R. 12E W.M.
Bearing and distance from section or subdivision corner
1285 FT. SOUTH 9-135.3 FT. WEST FROM THE
NE CORNER OF —

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft.
Static level 197 ft. below land surface. Date 12-20-73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"

Depth drilled 427 ft. Depth of completed well 427 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
OPEN HOLE UP FROM SIX INCH TO 8 INCH DIA. 240 FT. TO 427 FT.			
CLAY YELLOW SANDY	240	282	197
BASALT DARK GRAY HARD	282	424	197
BASALT (VESICULAR) BLACK	424	427	197
WATER-BEARING			

Work started 12-9 1973 Completed 12-19 1973
Date well drilling machine moved off of well 12-20- 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Bob G. Hill Date 12-20 1973
(Drilling Machine Operator)

Drilling Machine Operator's License No. 589

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name RONALD D. EDSELL
(Person, firm or corporation) (Type or print)

Address P.O. BOX 695 CASTLE ROCK, WASH. 98611

[Signed] Ronald D. Edsell
(Water Well Contractor)

Contractor's License No. 515 Date 12-20, 1973