NOTICE TO WATER WELL CONTENT OF CELVE The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, ORESTANTE ENGINEERE OF OREGON within 30 days from the date SALEM. OREGON to write above this line of well completion.

•	State Well No.	<u>o</u>
	State Permit No.	r'en d'en ein Mane

(1) OWNER:	(11) LOCATION OF WELL:		
Name Mr.Stewart Loyd	County Wasco Driller's well number		
Address Mosier, Ore.	14 14 Section 18 12 N. R. 12 E. W.M.		
The state of the s	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	and distance from section of subdivision corner		
New Well	***		
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing 8th		
Rotary Driven Domestic Lindustrial Municipal Domestic	The state of the s		
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Depth drilled 342 ft. Depth of completed well 342 ft.		
CASING INSTALLED: Threaded □ Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
O Diam from O tt to 321611 tt care .250	with at least one entry for each change of formation. Report each change		
" Diam. fromft. toft. Gage	in position of Static Water Level as drilling proceeds. Note drilling rates.		
" Diam. fromft. toft. Gage	MATERIAL From To SWL		
	Soil 0 4  Blow Sand 4 25		
PERFORATIONS: Perforated?   Yes   No.	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		
e of perforator used			
Size of perforations in by in.			
perforations fromft. toft.			
perforations fromft. toft.			
perforations from ft. to ft.			
perforations from	Grey sandstone 64 79 Brown sandstone 79 86		
perforations from ft. to ft.	Grey sandstone 86 100		
(F) CORRENG	Granite boulders 100 135		
mountained. [] 165 [] 140	Jt. clay, cream colored 135 146		
Manufacturer's Name	Granite boulders 146 159		
Type Model No.	Blue grey basalt 159 290		
Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft.	Black rock, trace of		
Set from ft. to ft.	clay 290 336		
(8) WATER LEVEL: Completed well.	Grey basalt 336 342		
Static level 192 ft. below land surface Date , 16,68			
ian pressure lbs. per square inch Date			
(9) WELL TESTS: Drawdown is amount water level is			
lowered below static level			
Was a pump test made? K Yes □ No If yes, by whom? Driller	2 22		
Yield: 15 gal./min. with 40 ft. drawdown after 4 hrs.	Work started 2,28 158 complete6,18 1968		
" " " " " " " " " " " " " " " " " " "	Date well drilling machine moved off of well 6.20 1968		
" " " " " " " " " " " " " " " " " " "	Drilling Machine Operator's Certification:		
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my direct supervision. Mate-		
Artesian flow g.p.m. Date 6.20.68 —	rials used and information reported above are true to my best knowledge and belief.		
Temperature of water 54 Was a chemical analysis made? ☐ Yes ☑ No	[Signed] Best Clayton Date 7/12 1968		
(10) CONSTRUCTION:	(Drilling Machine Operator)		
Well seal-Material used Bentonite	Drilling Machine Operator's License No. 140		
Depth of sealft	Water Well Contractor's Certification:		
Diameter of well bore to bottom of seal 10 in.	This well was drilled under my jurisdiction and this report is		
Were any loose strata cemented off?  Yes  No Depth	true to the best of my knowledge and belief.		
Was a drive shoe used? ☐ Yes □ No	NAME Bert Clayton & Son		
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 2313 E. 10th The Dalles, Ore.		
fethod of sealing strata off			
Was well gravel packed? ☐ Yes ☑ No Size of gravel:			
Gravel placed fromft. toft. Contractor's License No. 54 Date 7.121968			
	1900		