

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

RECEIVED

STATE OF OREGON
(Please type or print)

WASCO

State Well No. 2N12E-18b2
State Permit No. G-9795 (well #2)

JAN 27 1978 (Do not write above this line)

003028

WATER RESOURCES DEPT.
SALEM, OREGON

(1) OWNER:

Name Paul Brooks
Address Mosier, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

8" Diam. from 0 ft. to 139 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
0 gal min air test with "100% drawdown at 460' "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 0 sacks
How was cement grout placed?
3 sacks

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Wasco Driller's well number
NE 1/4 NW 1/4 Section 18 T.2N R. 12E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 210 ft.
Static level 217 ft. below land surface. Date 17 Jan
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8
Depth drilled 460 ft. Depth of completed well 460 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil	0	7	
Sand	7	36	
Sandstone tan	36	72	
Cobles	72	78	
Clay gray	78	102	
Sandstone gray	102	123	
Basalt gray WB	123	275	
Rock gray & green WB	275	390	
Basalt gray visic. WB	390	460	217

Work started 7 Jan 1978 completed 17 Jan 1978
Date well drilling machine moved off of well 17 Jan 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Richard J. Murray Date 23 Jan, 1978
(Drilling Machine Operator)

Drilling Machine Operator's License No. 737

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Richard J. Murray
(Person, firm or corporation) (Type or print)

Address 3712 W. 8th The Dalles, Oregon

[Signed] Richard J. Murray
(Water Well Contractor)

Contractor's License No. 606 Date 23 Jan, 1978