NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON

(Please type or print)

003040 (Do not write above this line)

RECEIVED AUG 30 1978 WATER RESOURCES DEPT. SALEM

State Well No. 2N/12E-19G

State Permit No.

(1) OWNER:

Name Roger S. Snow

Address P.O. Box 519
Mosier, OR. 97040

(2) TYPE OF WORK (check):

New Well XX Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒

6" Diam. from +1 ft. to 79 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom?

Yield: 45 gal./min. with 51 ft. drawdown after 2 hrs.
" " "
" Air Lift Pump " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement Grout

Well sealed from land surface to 52 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal 28 sacks

How was cement grout placed? poured

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes XX No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Wasco Driller's well number 78-24

NW ¼NW ¼ Section 19 T. 2N R. 12 E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 87 ft.

Static level 18 ft. below land surface. Date 8/10/78

Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"

Depth drilled 127 ft. Depth of completed well 125 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. **Report each change in position of Static Water Level and indicate principal water-bearing strata.**

MATERIAL	From	To	SWL
Clay brown with boulders	0	47	
Basalt grey hard	47	65	
Basalt grey fractured	65	87	
Basalt grey fractured WB	87	125	18

Work started 8 Aug 1978 Completed 11 Aug 1978

Date well drilling machine moved off of well 12 Aug 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] William Lee (Drilling Machine Operator) Date 29 Aug, 1978

Drilling Machine Operator's License No. 700

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Marinelli Drilling Co. (Person, firm or corporation) (Type or print)

Address P.O. Box 571, Lake Oswego, OR. 97034

[Signed] (Water Well Contractor)

Contractor's License No. 672 Date 29 Aug., 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119