

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED

WASC

WATER WELL REPORT

STATE OF OREGON

MAY 28 1974

State Well No.

2N/12E-22

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

003131

(Please type or print)

STATE ENGINEER

State Permit No.

SALEM, OREGON

(1) OWNER:

Name Samuel Decker
Address Route 4, Box 210
The Dalles, Oregon 97058

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal []
Irrigation [X] Test Well [] Other []

(5) CASING INSTALLED:

6" Diam. from 0 ft. to 41 ft. Gage 250
Threaded [] Welded [X]

(6) PERFORATIONS:

Perforated? [] Yes [X] No
Type of perforator used
Size of perforations in. by in.

(7) SCREENS:

Well screen installed? [] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Air Bailer test 50 gal./min. with 100 ft. drawdown after 9 hrs.

(9) CONSTRUCTION:

Well seal-Material used Bentonite - cement
Well sealed from land surface to 40 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 4 sacks
Number of sacks of bentonite used in well seal 2 sacks
Brand name of bentonite Yellowstone
Number of pounds of bentonite per 100 gallons of water 65 lbs./100 gals.
Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Wasco Driller's well number
NW 1/4 SW 1/4 Section 22 T. 2N R. 12 E. W.M.
Bearing and distance from section or subdivision corner 120' south from center of Seven Mile Hill county road.

(11) WATER LEVEL: Completed well.

Depth at which water was first found 25 ft.
Static level 33 ft. below land surface. Date 5-14-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"
Depth drilled 320 ft. Depth of completed well 320 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Soil, brown clay; Rock, decomposed; Rock, broken; Rock, grey; Rock, black; Rock, grey; Rock, grey-green, clay seams; Rock, red porous; Rock, grey porous, pyrites; Rock, grey.

Work started May 2 1974 Completed May 13 1974
Date well drilling machine moved off of well May 14 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Gilbert Clayton Date May 25, 1974
(Drilling Machine Operator)

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Gilbert Clayton Well Drilling (Type or print)
Address Rt 1, Box 61-A, The Dalles, Oregon
[Signed] Gilbert Clayton (Water Well Contractor)
Contractor's License No. 569 Date May 25, 1974