NOTICE TO WATER WELL CONTRACTOR The original and first coby of this report are to b			in do
filed with the STATE OF STATE ENGINEER, SALEM, ORIGON 97310 (Please typ within 30 days from the date of well completion. 003239 (Do not write a	OT I HAVE AND	<u>2N/13E -</u> 10.	19 ac
(1) OWNER:	(10) LOCATION OF WELL:		
	County Wasco Driller's well number		
Address Route 4, Box 215-A, The Dalles, On	"C - SW 1/4 SE 1/4 Section 19 T. 2N R. 13 E.W.M.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New Well Deepening 2. Reconditioning Abandon D If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found ft.		
Rotary K Driven D Domestic K Industrial D Municipal			ft.
Cable Image: Definition of the state of			19-15
	(12) WELL LOG: Diameter of well below casing 6"		
	Depth drilled 140 ft. Depth of completed well 375 ft.		
	Formation: Describe color, texture, grain size and structure of materials;		
	and show thickness and nature of each stratum with at least one entry for each change of forma	tion. Report each c	hange in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-bearin	g strata.
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Rock, green clay seams	235 320	60
perforations from ft. to ft.	decomposed rock, packed		
perforations from ft. to ft.	blow sand	320 320 1	92
ft. to ft.	Rock, porous black	320불 335	92
(7) SCREENS: Well screen installed?	Rock, porous black, hard	335 369	<u> 253 </u>
Manufacturer's Name	Rock, gray flakes, hard	369 375	<u> 253 </u>
Type Model No.		┨────┤────┤	·
Diam Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.			······································
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			·····
Was a pump test made? Yes DNo If yes, by whom? Driller		<u> </u>	
" " " " "			
Poilor test			
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started Feb. 3 1975 Complete	ed Feb. 20	19 75
(9) CONSTRUCTION:	Date well drilling machine moved off of well	Feb. 20,	<u>19 7</u> 5
Well seal-Material used same seal - Bentonite	Drilling Machine Operator's Certification:		
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of seal in.	best knowledge and belief.		
Diameter of well bore below seal in.	[Signed]		
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. <u>129</u>		
Number of sacks of bentonite used in well seal	brinning Machinie Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Yes No Plugs	true to the best of my knowledge and belief.		
Did any strata contain unusable water? 🗌 Yes K No	Name Gilbert Clayton Well Drilling		
Type of water? depth of strata	Address Rt 1, Box 61-A, The Dalles, Ore.9705		
Method of sealing strata off	BIN FOIR		
Was well gravel packed? [] Yes 2 No Size of gravel:	[Signed](Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 569 Date 3	3-1/2-75	10
(USE ADDITIONAL SH			, 1,9
COR ADDITIONAL SH	LILL IN MEDICOMICI	SP	*45656-119

٣,