State Well No.

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

MAY 3 WATER WELL REPO

MAY 3 WATER WELL REPO

OF OREGON

STATE ENGINEER, SALEM 10, OREGON

WITHIN 30 days from the date of well completion.

003278

of well completion.	TOTAL TRANSPORT	Diate 2 crime No		
(1) OWNER: Name Rudy R.Walters		(11) WELL TESTS: Drawdown is amount value of the property of t	vaten leve vel 52 r n? Str	rön & iyer
Address Route #4 Box 117		Yield: 220 gal./min. with 3 ft. drawdow		
The Dalles, Oregon.		" " "		**
-		;; ;; ;; ;;		***
(2) LOCATION OF WELL:		Bailer test gal./min. with ft. drawdov	n after	hrs.
County Sherman MASCO Driller's well number		Artesian flow g.p.m. Date		
14 14 Section 19-30T.2N R. 13E W.M.		Temperature of water Was a chemical analysis r	nade? 🔲 🦪	Yes Tr No
Bearing and distance from section or subdivisi				
50ft. north of Chenowi	th Road, 100ft.	(12) WELL LOG: Diameter of well below c	asing	1.0.11
West of Brown Creek Road.		Depth drilled 605 ft. Depth of completed w	ell 601	5 ft.
		Formation: Describe by color, character, size of materic show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	l and stru the mater hange of	cture, and lal in each formation.
		MATERIAL	FROM	то
(3) TYPE OF WORK (check):		clay, gravel, boulders	0	44
New Well Deepening Reconditioning Abandon and and procedure in Item 12.		pours gray rock & clay	44	¥-89
		sticky gray clay at 100ft.	77.7	-93
			89	100
(4) PROPOSED USE (check):	(5) TYPE OF WELL:	some water at 110 ft.		129
Domestic Industrial Municipal X	Rotary 🔟 Driven 🗍	gray clay, some gray rock	129_	144
Irrigation Test Well Other	Cable Jetted	broken gray basalt, clay sear		4.60
migation [] Test Wen [] Other []	Dug 🗌 Bored 🗍	1 11 11 11 11 11	144	160
(6) CASING INSTALLED: The	eaded Welded		160	253_
12 " Diam. from 30 ft. to		green clay, sticky	253	285
10 "Diam. from 0 ft. to 48		broken basalt, green clay	285	355
		greenclay	355	380
" Diam. from ft, Gage ft, Gage		brown rock with clay seams	380	395_
(7) PERFORATIONS: Perforated? ☐ Yes ☐ No			395	420
Type of perforator used	- -	green sticky clay	420	480
Size of perforations in. by in.		hard black basalt rock		
perforations from		crevices , some clay	480	560
perforations from		same formation, some water		
perforations from		between 595 and 605	560	605
perforations from				
		Pulled pipe back into clay		
perforations from	ft. to ft.	at 50feet which made a firm		
(8) SCREENS: Well screen ins	stalled Tyes X No	seal under ground.		
Manufacturer's Name	2 200 1200	Scar ander ground.		
Mo	del No			
Slot size Set from ft, to ft.		War of Marach OZo 61 completed As	0 = 0 4 7 (21: 10 60
Diam. Slot size Set from ft. to ft.				24 19 62
Didit		Date well drilling machine moved off of well Apr	1 24	1962
(9) CONSTRUCTION: Drove sl	hoe into rock	(13) PUMP:		
Well seal-Material used in sealBailed_well_dry		Manufacturer's Name		
Depth of seal 50-480 ft. Was a packer used?		Type: H.P.		
Diameter of well bore to bottom of seal 1.2-1.0 in.				
Were any loose strata cemented off? Wes 50 Depth 495-505		Water Well Contractor's Certification:		
Was a drive shoe used? Yes. \(\) No		This well was drilled under my jurisdiction and this report is		
Was well gravel packed? Yes No Size of gravel:		true to the best of my knowledge and belief.		
Gravel placed from ft. to ft.		Pompon & Ct		
		NAME Barron & Strayer (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? A Yes No Type of water? Brackish Depth of strata 480		i e e e e e e e e e e e e e e e e e e e		
		Address Route #1 Box 254, Beaverton, Ore.		
Method of sealing strata off Pipe		Drilling Machine Operator's License No.		
(10) WATER LEVELS:		0 71 Pari		
Static level 372 ft. below land surface Date 4/3/62		[Signed] (Water Well Contractor)		
				10 -
Artesian pressure lbs. per squa	are men Date	Contractor's License No. 35. Date Maj	726	, 19 6 .2