NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the		2N/14E-2Lar	
STATE ENGINEER, SALEM, OREGON 97310 JAN 10 (Please type within 30 days from the date of well completion.	or print) ()()3340	0.	
VIALEM OFFCON			
(1) OWNER:	(10) LOCATION OF WELL:		
Name Jacob Kaser	County Wasco Driller's well nu	imber	
Address Rt 3. Box 85	- SW 14 NE 14 Section 26 T. 2N	R. 14 E. W.M.	
<u>The Dalles, OR 97058</u>	= Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(II) WATER LEVEL: Completed wen.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 18 ft.		
Rotary X Driven CPhle A Jetted D Domestic D Industrial Municipal D	Static level 15 ft. below land s	urface. Date 12-23-77	
Bored D Irrigation F Test Well D Other	Artesian pressure Ibs. per squar	e inch. Date	
(5) CASING INSTALLED: Threaded Welded X (12) WELL LOG: Diameter of well below casing 8" 8 "Diam. from 0 ft. to 38 ft. Gage 250 ft. Depth drilled 165 ft Depth of completed well 155 ft.			
" Diam. from	Depth drilled 165 ft. Depth of compl	eted well 155 ft.	
"Diam. from	Formation: Describe color, texture, grain size a		
with at least one entry for each change of formation. Report each change in			
(6) PERFORATIONS: Perforated?  Yes X No.	position of Static Water Level and indicate prin	cipal water-bearing strata.	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Soil, sandy	0 2	
	Boulders, bonded	2 18 13	
perforations from ft. to ft. to	Gravel	18 33 13	
perforations from ft. to ft.	Rock, grey	33 50	
(7) SCREENS: Well screen installed?	Rock, decomposed	50 60	
(7) SCREENS: Well screen installed? □ Yes K No Manufacturer's Name	Rock, grey /seams		
Type Model No.	HOCK, STEV	70 150	
Diam Slot size Set from ft. to ft.	Rock, grey/seams Rock, decomposed	155 165 15	
Diam	100A: Geoomposed		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Grouted formation from		
Was a pump test made? 🗌 Yes 🔏 No If yes, by whom?	50 to 60 ft, formation	· · · · · · · · · · · · · · · · · · ·	
d: gal./min. with ft. drawdown after hrs.	unstable.		
n " "			
<u> </u>			
Air Bailer_test 300 gal./min. with 85ft. drawdown after 2 hrs.			
sian flow g.p.m.		· · · ·	
Temperature of water 56 Depth artesian flow encountered ft.	Work started NOV. 30 1977 Complet	ed Dec. 22 19 77	
	Date well drilling machine moved off of well		
(9) CONSTRUCTION:		· · · · · · · · · · · · · · · · · · ·	
Well seal-Material used Cement grout	Drilling Machine Operator's Certification: This well was constructed under my		
Well sealed from land surface to36	Materials used and information reported	above are true to my	
Diameter of well bore to bottom of seal	best knowledge and belief,		
Diameter of well bore below seal	[Signed]		
Number of sacks of cement used in well seal	Drilling Machine Operator's License No.	129	
Number of sacks of bentonite used in well seal 110110 Brand name of bentonite			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
f water lbs./100 gals. This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? 🕅 Yes 🔲 No Plugs	drive shoe used? A Yes D No Plugs Size: location ft. Name Gilbert Clayton Well Drilling		
Did any strata contain unusable water? 🔲 Yes 🕅 No 💠	Rt 1, Box 61-A, The Dalles, OR 97058		
Type of water? depth of strata	Address		
Method of sealing strata off	[Signed] Silvert Clay	In	
Was well gravel packed? 🗌 Yes 🎽 No Size of gravel:	(Water Well Cont		
Gravel placed from ft. to ft. to ft. Contractor's License No Date 12-30-77, 19			
(USE ADDITIONAL S	HEETS IF NECESSARY)	SP*45658-119	