NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT WASIC

STATE OF OREGON

(Do not write above this line)

(Please type or print)

State Well No. 15/13E - 71 bc

003418 State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:			
Nathe Carl L. & Elaine K. Ingram	County WASCO Driller's well number 79-20			
Address 1707 Riverview	SW 1/4 NW 4 Section 21 T.1S R. 13 E. W.M.			
The Dalles, OR. 97034	Bearing and distance from section or subdivisi	on corne	r	
(2) TYPE OF WORK (check):	Tax Lot 3490			
New Well				-
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	الم		-
(3) TYPE OF WELL: (4) PROPOSED USE (check):				
			–	ft.
Rotary Z Driven D Domestic K Industrial Municipal D Dug Bored D Irrigation Test Well Other	Static level 43 ft. below land s			[24] 19
200 E 201cd E 201gaton E 1050 Hen E Onter	Artesian pressure lbs. per squar	e inch.	Date	
CASING INSTALLED: Threaded Welded XX	(12) WELL LOG: Diameter of well h			~11
	The state of the s			
"Diam. fromft. toft. Gage				-
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratus	m and a	guifer r	enetrated.
PERFORATIONS: Perforated? Tyes W No.	with at least one entry for each change of format position of Static Water Level and indicate prin	tion. Rep	ort each	change in
Total and Total Mario.		cipai wa	ter-pear	ng strata.
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	Clay brown	0	12	
perforations from ft. to ft.	Clay -Gravel	12	18	ļ
perforations from ft. to ft.	Sandstone brown	18	_34	<u> </u>
perforations from ft. to ft.	Clay brown	34	48	<u> </u>
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Sàndstone brown WB	48	90	51
Manufacturer's Name	Cinder red w/clay	98	94	ļ
Type Model No.	Lava black & red fractured WB	94	98	43
Diam. Slot size Set from ft. to ft.	Cinder red	98	100	
Diam. Slot size from ft. to ft.	Conglomerates	100	112	
	Basalt grey w/ fracturees	112 172	172	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Basalt grey Basalt grey Fractured WB	183	183 223	43
Was a pump test made? ▼ Yes □ No If yes, by whom? Driller	DROGIC GLEY FIACCULED ND	103	463	147
yeld: 50 gal./min. with 131 ft. drawdown after 2 hrs.				
" " " "	WELFIVE II			
" Air Lift Pump " "				
Dellar test	AUG9 = 1979		~	
A. d. d. m	WATER RESOURCES DEPT			
Artesian flow g.p.m.	·· •			
perature of water 64 Depth artesian flow encountered ft.	Work started 7/21 1979 Complete			19 79
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7/2	4	19 79
Well seal—Material used Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface to 25 ft.	This well was constructed under my	direct	super	vision.
Diameter of well bore to bottom of seal 12 in.	Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore below sealin.		D-4-	916	10.70
Number of sacks of cement used in well sealsacks	[Signed] Date 8/6 , 19.79			
How was cement grout placed?	Drilling Machine Operator's License No. 700			
The which is a state of the sta	TOTAL STATE OF THE			
Pumped	Water Well Contractor's Certification:			4.
	This well was drilled under my jurisdictrue to the best of my knowledge and beli	ction an ef.	d this	eport is
Was a drive shoe used? W Yes 🗌 No Plugs Size: location ft.	Name Marinelli Drilling Co.			
Did any strata contain unusable water? Tyes X No	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address P.O. Box 571 Lake Oswego	OR.	9703	4
Method of sealing strata off	reimade To		m[]	7
Was well gravel packed? [] Yes YNo Size of gravel:	[Signed] (Water Well Contra	etor)		***********
Gravel placed fromft. toft.	er in the second of the second	8/6		19 79
	TOWN DESCRIPTION AND AND AND AND AND AND AND AND AND AN		****	, то