NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE OF	L REPORT EIVED OBEGON NOUL STATE Well No. 13/13E-25 da
state Well No. 3/32-25 da state Well No. 3/32-25 da state Well No. 3/32-25 da state Well No. 3/32-25 da (Please type or print) within 30 days from the date of well completion. (Do not write above this line) CCURCES DET	
(1) OWNER:	(10) LOCATION OF WELL:
Name Wilbur J. Petersen	County Wasco Driller's well number
Address 1518 Meadow Ave.	NE 1/4 SE 1/4 Section 25 T. 1 S R. 13 E.W.M.
Stockton, Calif,	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🕅 Deepening 🗌 Reconditioning 🗌 Abandon 🗌	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 40 ft.
Determ W Determ	11 06 776
Cable D Jetted D Domestic D Industrial D Municipal	
Dug 🗌 Bored 🗍 Irrigation 🗌 Test Well 🗛 Other 🗌	Artesian pressure Ibs. per square inch. Date
(5) CASING INSTALLED: Threaded □ Welded X 6 "Diam. from 0 ft. to 26 ft. Gage .250	(12) WELL LOG: Diameter of well below casing6" Depth drilled 210 ft. Depth of completed well 210 ft.
"Diam. from ft. to ftGage	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated? Yes X No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Rock, decomposed 0 25
perforations from ft, to ft.	Rock, grey 25 40
perforations from ft. to ft.	Rock, porous-grey 40 55 6
perforations from ft. to ft.	Rock, grey 55 80 6
	Rock, red porous/quartz 80 90 6
(7) SCREENS: Well screen installed? Yes X No	Rock, grey-hard 90 195 6
Manufacturer's Name	Rock, porous/quartz 195 205 6
Type Model No.	Rock, grey 205 210 flowing
Diam	Closed flow off with plug and
Diam Slot size Set from ft. to ft.	grouted well at 185 feet.
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Will ream well in spring and grout cas:
Was a pump test made? Ves Ves If yes, by whom?	in to 185 feet.
d: gal./min. with ft. drawdown after hrs.	
	Well is capped and will not be used
<u>" " " " " " " " " " " " " " " " " " " </u>	until properly constructed.
Bailer test gal./min. with ft. drawdown after hrs.	
desian flow g.p.m.	
supperature of water 56° Depth artesian flow encountered ft.	Work started November 1976 Completed Nov. 26 1976
(9) CONSTRUCTION:	Date well drilling machine moved off of well NOV. 26 1976
Well seal-Material used Cement Grout & Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface to25ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal	[Signed] Supert Anyton Date Nov 28, 19 76
Number of sacks of cement used in well seal 2	(Drilling Machine Operator)
Number of spake of bontonite used in well seal 2 sacks	Drilling Machine Operator's License No. 129
Brand name of bentoniteYellowstone	Weter Well Contractor's Contification
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? X Yes D No Plugs Size: location ft.	Name Gilbert Clayton Well Drilling
Did any strata contain unusable water? 🔲 Yes 🏳 No	(Demon Sime on comparation) (Thung on print)
Type of water? depth of strata	Address Rt 1, Box 61-A, The Dalles, OR 9705
Method of sealing strata off	simul Albert I lant
Was well gravel packed? [] Yes [] No Size of gravel:	[Signed]
Gravel placed from ft. to ft.	
(USE ADDITIONAL S	HEETS IF NECESSARY)