NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

(Please type or print)

(Do not write above this line) 003428

tate	Well No	, 15/13E-25 dea	_
		despend	
tate	Permit		

(1) OWNER:	(10) LOCATION OF WELL:		
Name Wilbur J. Petersen	County Wasco Driller's well number		
Address 1518 Meadow Ave.	NE 1/4 SE 1/4 Section 25 T. 1 S R. 13 E.W.M.		
Stockton, Calif. 95207	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	-		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.		
Rotary Driven Domestic Industrial Municipal	Static level ft. below land surface. Date		
Cable Jetted Bornest Industrial Indu	Artesian pressure 75 lbs. per square inch. Date 8-15-80		
CASING INSTALLED: 1977 Welded	(12) WELL LOG: Diameter of well below casing 10 ¹¹		
	Depth drilled 43 ft. Depth of completed well 341 ft.		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;		
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,		
PERFORATIONS: Perforated?	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	Rock, grey/pyrites 298 305		
perforations fromft. toft.	Rock, grey, hard/seams 305 318		
perforations fromft. toft.	Clay, black & green 318 328		
perforations from ft. to ft.	Rock, grey/quartz 328 339		
(A) COMPENIO	Clay, loose, black & green339 341		
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name			
Type Model No Diam Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
The same state of the same sta			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	PLOS		
a pump test made? Yes No If yes, by whom?			
d: gal./min. with ft. drawdown after hrs.	272		
" " "	WATER 171980		
n n n			
Air tot 350	SALEM, OREGON		
	- TEGON		
sian flow 45 g.p.m. sperature of water 56 bepth artesian flow encounteredft.	Work started Aug. 12 19 80 completed Aug. 15 19 80		
	Date well drilling machine moved off of well Aug. 15 19 80		
(9) CONSTRUCTION: Well seal-Material used Well sealed in 1977			
· · · · · · · · · · · · · · · · · · ·	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of sealin. Diameter of well bore below sealin.	best knowledge and belief. [Signed] Sept. 15 1980		
Number of sacks of cement used in well sealsacks	[Signed] Date 1980		
How was cement grout placed?	Drilling Machine Operator's License No129		
	- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	NameGilbert Clayton Well Drilling		
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address Rt 1, Box 61-A, The Dalles, OR 9705		
Method of sealing strata off	[Signed]		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 569 Date Sept. 15 19 80		