

The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT WASC

STATE OF OREGON

State Well No. 15/13E-25da

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date

of well completion.

WATER RESOURCES DEPT.

(Please type or print)

Do not write above this line

003430

State Permit No.

SALEM, OREGON

(1) OWNER:

Name Wilbur J. Petersen

Address 1518 Meadow Ave. Stockton, California 95207

(2) TYPE OF WORK (check):

New Well [] Deepening [X] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [] Cable [] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [X] Test Well [] Other []

CASING INSTALLED:

8" Diam. from 0 ft. to 97 1/2 ft. Gage 250

PERFORATIONS:

Perforated? [] Yes [X] No

Type of perforator used

Table with 3 columns: Size of perforations, in. by, in. ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name, Type, Model No., Diam., Slot size, Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs. Bailer test 600 gal./min. with 0 ft. drawdown after 1 hrs. Artesian flow 450 g.p.m. Temperature of water 56° Depth artesian flow encountered 110 ft.

(9) CONSTRUCTION:

Well seal—Material used Well capped & grouted 1-22-71 Well sealed from land surface to ft. Diameter of well bore to bottom of seal in. Diameter of well bore below seal in. Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal sacks Brand name of bentonite Number of pounds of bentonite per 100 gallons of water lbs./100 gals. Was a drive shoe used? [X] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Wasco Driller's well number NE 1/4 SE 1/4 Section 25 T. 1 S.R. 13 E. W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft. Static level flowing ft. below land surface. Date Artesian pressure 71 lbs. per square inch. Date 11-25-78

(12) WELL LOG:

Diameter of well below casing 8" Depth drilled 75 ft. Depth of completed well 200 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include Rock, black/brown flakes, Rock, brown porous, Rock, grey porous, Rock, brown porous, Rock, grey porous.

Work started Nov. 7 1978 Completed Nov. 8 1978

Date well drilling machine moved off of well Nov. 8 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Gilbert Clayton Date 12-1-78 (Drilling Machine Operator)

Drilling Machine Operator's License No. 129

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Gilbert Clayton Well Drilling (Person, firm or corporation) (Type or print) Address Rt. 1, Box 61-A, The Dalles, OR 97058

[Signed] Gilbert Clayton (Water Well Contractor)

Contractor's License No. 569 Date Dec. 1, 1978