## NOTICE O WATER WELL CONTRACTOR the original and first copy of this report are to be filed with the

## WATER WELL REPORT WASE

state engineer, salem, oregon 9731R ECE VPlaset pe or print) within 30 days from the date of well completion.

(Do not write above this 10 3451

State	Well No.	15/1	38-	34	acb
~		-		_	

(1) OWNER: WATER RESOURCES DEP	(10) LOCATION OF WELL:			
Name Kenneth Purdom SALEM, OREGON	County Wasco Driller's well nu	mber		
Address 2260S Indian Creek Rd.	NW % NE % Section 34 T. 1S	R. 13F. W.M.		
Diamond Bar, Ca. 91765	Bearing and distance from section or subdivisi			
(2) TYPE OF WORK (check):				
New Well   ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 82	· <u></u>		
Rotary M Driven Domestic Industrial Municipal		ft.		
Cable	Static level 1t. below land 8			
	Artesian pressure 30 lbs. per squar	e inch. Date 28 June		
(5) CASING INSTALLED: Threaded [] Welded []	(12) WELL LOG: Diameter of well b	elow casing 10		
10 " Diam. from 0 ft. to 398 ft. Gage • 250	Depth drilled 565 ft. Depth of comple			
ft. to ft. Gage	Formation: Describe color, texture, grain size a			
"Diam. fromft. toft. Gage	and show thickness and nature of each stratur	n and aquifer penetrated,		
PERFORATIONS: Perforated?   Yes   TV No.	with at least one entry for each change of format position of Static Water Level and indicate prin			
Type of perforator used	TEATHERY			
	MATERIAL	From To SWL		
Size of perforations in. by in.	Soil	0 13		
perforations fromft. toft.	Sandstone	13 72		
perforations fromft. toft.	Basalt gray hard Gravel med WB	82 94 72 82		
perforations from ft. to ft.	Basaly gray green	84 156		
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	Basalt soft broken WB	156 163		
Manufacturer's Name	Basalt gray hard	163 183		
Type Model No	Basalt brown	183 186		
Diam ft. to ft.	Clay brown	186 194		
Diam, Slot size Set from ft. to ft.	Basalt gray WB	194 277		
(8) WELL TESTS: Drawdown is amount water level is	Basalt brown broken	277 281		
lowered below static level	Basalt gray hard	281 422		
Was a pump test made? ∑ Yes ☐ No If yes, by whom?	Basalt gray fracturedWB	422 428		
Vield: 300 gal./min. with 410 ft. drawdown after 2 hrs.	Basalt gray	428 462		
" " " " " " " " " " " " " " " " " " "	Basalt black	462 468		
H H H	Basalt gray Basalt black soft	468 473		
Bailer test gal./min. with ft. drawdown after hrs.	Basalt brown	473 475 475 5 <b>2</b> 5		
Artesian flow 150 g.p.m.	Basalt & cobles	5 <b>7</b> 5 534		
hperature of water Depth artesian flow encountered 422 ft.	Work started 28 March1977 Complete			
(9) CONSTRUCTION:	Date well drilling machine moved off of well	28 June 19 77		
Well seal—Material usedCement	Drilling Machine Operator's Certification:	,		
Well sealed from land surface to 398	This well was constructed under my	direct supervision.		
Diameter of well bore to bottom of seal 16. to 7/2 then 398	Materials used and information reported best knowledge and belief.	above are true to my		
Diameter of well bore below seal10 in.	[Signed] (Pickard Musican	Data C / O.O 1077		
Number of sacks of cement used in well seal85sacks	[Signed] Proham Machine Operator)	Jane		
Number of sacks of bentonite used in well seal Sacks	Drilling Machine Operator's License No	737		
Brand name of bentonite	Water Wall Contractor's Contification			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	Man and Witness and		
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? ☐ Yes XXNo Plugs Size: location ft.	Name Richard J. Murray			
Did any strata contain unusable water? 🗌 Yes 🗶 No	(Person, firm or corporation)	(Type or print)		
Type of water? depth of strata	Address 3712 W 8th The Dal	res, oregon		
Method of sealing strata off	[Signed] Richard Mounts	W)		
Was well gravel packed? ☐ Yes [Y No Size of gravel:		(%) cybr)		
Gravel placed from ft. to ft.	Contractor's License No. 606 Date	29 June , <sub>19</sub> 77		

## TO WATER WELL CONTRACTOR The original and first copy of this report are to be

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON (Please type or print)

(Do not write above this line)

	15/138-34ah
State Well No.	

State Permit No. ....

(1) OWNER:	(10) LOCATION OF WELL:
Vame -	County Driller's well number
Address	14 14 Section T. R. W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	176 T
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Domestic   Industrial   Municipal   Domestic   Industrial   Municipal   Domestic   Test Well   Other	Static level ft. below land surface. Date  Artesian pressure lbs. per square inch. Date
*CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing
" Diam. fromft. toft. Gage	
" Diam. from ft. to ft. Gage	Deput dimed
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?   Yes   No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
	Sand & claystone green WB
perforations fromft. toft.	caving. 534 565
perforations fromft. toft.	Drilled 14" hole to 398' then set
(7) SCREENS: Well screen installed?   Yes   No	10" pipe and presure grouted with
Manufacturer's Name	85 sacks of cement with the use of
Type Model No	a grout pump. Then drilled deeper.
Diam Slot size Set from ft. to ft.	If this hole is deepened an eight inch
Diam Slot size Set from ft. to ft.	casing should be installed to control
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	the caving situation.
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
n " " " " " " " " " " " " " " " " " " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 19 Completed 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 19
Well seal—Material used	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief
Diameter of well bore below seal in.	[Signed] (Drilling Magnine Operator) Date, 19
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	the test of mer length of and holief
Was a drive shoc used?   Yes   No Plugs   Size: location ft.	Name (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes _ No	
Type of water? depth of strata	Address
Method of sealing strata off	[Signed](Water Well Contractor)
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	
Gravel placed from ft. to ft.	Contractor's License No