NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

RECENTED WELL REPORT WASE

STATE ENGINEER, SALEM, OREGON 97310 OCT 1 3 1977 Please type or print) OF 3 456 within 30 days from the date of well completion.

VATER RESOURCES DEPT.

KlIAT 271

State	Well No	HEDOU
State	Permit No.	

SALEM, OREGON	The second of the T		
(1) OWNEK:	(10) LOCATION OF WELL:		
Name Fax Brothers Ranch	County Wasco Driller's well num		<u> </u>
Address Rt 3, Box 32	SE 14 NÉ 14 Section 3 T. 1 S	R. 14	E.W.M.
The Dalles, OR 97058	Bearing and distance from section or subdivision	n corner	
(2) TYPE OF WORK (check):			
New Well 🚻 Deepening 🗌 Reconditioning 🗍 Abandon 🗌			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	:11.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 20		ft.
Rotary Driven Domestic Industrial Municipal	Static level ft. below land su	ırface. Date	
Cable	Artesian pressure 120 lbs. per square	inch. Dio	5-77
Sug			
CASING INSTALLED: Threaded Welded OF O	(12) WELL LOG: Diameter of well be		
10 " Diam. from 0 ft. to 118 ft. Gage .250	Depth drilled 281 ft. Depth of completed well 281 ft.		
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size as	nd structure	of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum with at least one entry for each change of formati	n and aquife:	r penetrated,
PERFORATIONS: Perforated? Yes X No.	position of Static Water Level and indicate princ	ipal water-b	earing strata.
	MATERIAL	From T	ro SWL
Type of perforator used	Soil, brown	0	6
Size of perforations in. by in.	Gravel	6 2	20
perforations fromft. toft.	Rock, broken		30
perforations from	Rock, grey	30 14	
perforations from ft. to ft.	shale, green	145 15	0 flowing
(7) SCREENS: Well screen installed? Yes X No	Rock, porous grey	150 18	32 flowing
Manufacturer's Name	Rock, grey porous w/white	182 20	07 "
Type Model No	flakes		
Diam. Slot size Set from ft. to ft.	Rock, grey	207 23	
Diam Slot size Set from ft. to ft.	Rock, porous black/quartz	230 26	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Rock, brown/yellow seams Rock, black/yellow seams	265 27 275 28	$\frac{1}{2}$
Was a pump test made? Yes No If yes, by whom?		1 7	
Yield: gal./min. with ft. drawdown after hrs.	Well capped with 10" Fla		
" " "	6" gate valve & pressure	gauge	
" " "			
Bailer test gal./min. with ft. drawdown after hrs.			
77.00			
Artesian flow 4.00 g.p.m. perature of water 59° Depth artesian flow encountered 145 ft.	Work started Aug. 23 19 77 Complete	ed Sept	15 19 77
	Date well drilling machine moved off of well	Sept :	15 19 77
(9) CONSTRUCTION:	Drilling Machine Operator's Certification:		
Well seal—Material used	This well was constructed under my	direct su	apervision.
Well sealed from land surface to 117 ft.	Materials used and information reported	above are	true to my
Diameter of well bore to bottom of seal 12 1/4 in.	best knowledge and belief.	Dat 10-6	-77 , ₁₉
Diameter of well bore below sealin. Number of sacks of cement used in well seal30sacks	(Drilling Machine Operator)		
214411004 04 040110 04 04110110 44041 141	Drilling Machine Operator's License No.	129	
Number of sacks of bentonite used in well sealsacks			
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my jurisd	iction and t	this report is
of water	true to the best of my knowledge and belief. Name Gilbert Clayton Well Drilling		
Did any strata contain unusable water? Yes X No	Name Rt 1, Box 61-A, The Dalles, OR 97058		
Type of water? depth of strata	Rt 1, Box 61-A, The De	TTTED,	011 31000
Method of sealing strata off	3111	2 K	
Was well gravel packed? ☐ Yes K No Size of gravel:	[Signed] (Water Well Cont		
Gravel placed from ft. to ft.	Contractor's License No. 569 Date	1 0-6-77	, 19
Graver praced from			