## WATER WELL REPORTWATER

STATE OF OREGON

State	Well	No.	15	)14E	-17bb

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the
STATE ENGINEER, SALEMOLEGON 731 V F
within 30 days from the date
of well completion. DEC - 1 1975

(Please type or print)
(Do not write above this line)

State Well No.	<u>/s</u>	114E	-17bb
State Permit N	Io	•	

(1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:		
Name Leo Schindl SALEM, OREGON	County Wasco Driller's well number		
Address Dufur, Oregon 97021	NW % NW % Section 17 T. 1S R. 14 E. W.M.		
THE THE PARTY OF T	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well □ Deepening ★ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	050		
Y			
Cable			
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing 6"		
" Diam. from 0 ft. to 36 ft. Gage .250	025		
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
DEDECORATIONS.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
PERFORATIONS: Perforated?   Yes X No.			
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	Rock, grey 35 192		
perforations from ft. to ft.	Opening 192 192 192 192 192 192 192 192 192 192		
perforations from ft. to ft.	Rock, broken 192‡ 202		
perforations from ft. to ft.	Rock, brown porous/yellow 202 217 Rock, grey porous Clay 217 232		
(7) SCREENS: Well screen installed?   Yes You no			
Manufacturer's Name	Rock, grey porous/green 232 237 245		
Type Model No.	Rock, grey hard 245 254 222		
Diam Slot size Set from ft. to ft.	Rock, porous/vellow & 254 257 222		
Diam Slot size Set from ft. to ft.	Rock, grey hard brown clay257 270 222		
(0)			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes 🛣 No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "			
A # 20			
Air EMEr test 15 gal./min. with 25 ft. drawdown after 1 hrs.			
Artesian flow g.p.m.			
perature of wate 58° Depth artesian flow encountered ft.	Work started Oct. 31 19 75 Completed Nov. 5 19 7		
(9) CONSTRUCTION:	Date well drilling machine moved off of well NOV. 5 19 7		
Well seal—Material used Bentonite	Drilling Machine Operator's Certification:		
27	This well was constructed under my direct supervision.		
Diameter of well bore to bottom of seal 2 in.	Materials used and information reported above are true to my best knowledge and belief,		
Diameter of well bore below seal in.	[Signed] Siffeed Laufer Date NOV. 28, 1975.		
Number of sacks of cement used in well seal none sacks	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal 11/2 sacks	Drilling Machine Operator's License No129		
Brand name of bentonite Yellowstone	Water Well Centractor's Configution		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water65 lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? ☐ Yes K No Plugs Size: location ft.	Name Gilbert Clayton Well Drilling		
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address Rt 1, Box 61-A, The Dalles, Ore.		
Method of sealing strata off	[Signed] Juliet Change		
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 569 Date Nov. 28 , 19 7		