

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

RECEIVED
WATER WELL REPORT
WASCO
AUG 10 1979
003467

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date of well completion.
STATE OF OREGON
(Please type or print)
WATER RESOURCES DEPT
Do not write above this line
SALEM, OREGON

State Well No. 1-114E-19ed
State Permit No. G-8835

(1) OWNER:
Name Wilbur J. Petersen

Address 1518 Meadow Avenue
Stockton, Calif. 95207

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: Rotary Driven
Cable Jetted
Dug Bored
(4) PROPOSED USE (check): Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED: Threaded Welded
6" Diam. from 0 ft. to 104 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow 100 g.p.m.
Temperature of water 56° Depth artesian flow encountered 96 ft.

(9) CONSTRUCTION:
Well seal—Material used Cement grout
Well sealed from land surface to 103 ft.
Diameter of well bore to bottom of seal 8 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 21 sacks
How was cement grout placed? pressure grouted
with grout pump
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Wasco Driller's well number
SE 1/4 SW 1/4 Section 19 T. 1 S R. 14 E. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 76 ft.
Static level flowing ft. below land surface. Date
Artesian pressure 82 lbs. per square inch. Date 6-22-79

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 225 ft. Depth of completed well 225 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil, Sandy	0	6	
Rock, decomposed	6	21	
Rock, hard grey	21	41	
Rock, red porous/whiteClay	41	56	
Rock, dark grey porous	56	76	
Rock, grey hard	76	90	6
Rock, grey broken, flowing	90	96	0
Rock, grey, hard	96	121	
Rock, grey	121	196	
Rock, porous grey	196	201	flowing
Rock, porous/quartz	201	206	"
Rock, porous, black	206	211	"
Rock, porous, grey	211	225	"

Work started June 13 19 79 Completed June 20 19 79
Date well drilling machine moved off of well June 20 19 79

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Gilbert Clayton Date 8-8-79, 19____
(Drilling Machine Operator)
Drilling Machine Operator's License No. 129

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Gilbert Clayton Well Drilling
(Person, firm or corporation) (Type or print)
Address Rt 1, Box 61-A, The Dalles, OR 97058
[Signed] Gilbert Clayton
(Water Well Contractor)
Contractor's License No. 569 Date 8-8-79, 19____