

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

WASCO

4/12-3ca

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

RECEIVED STATE ENGINEER SALEM, OREGON APR - 7 1970

STATE OF OREGON

Please type or print (Do not write above this line)

003553

State Well No.

State Permit No.

G5180

(1) OWNER:

Name Irl Davis Address Tygh Valley, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

10" Diam. from 0 ft. to 21 ft. Gage .025 6" Diam. from 0 ft. to 380 ft. Gage .025

(6) PERFORATIONS:

Perforated? [x] Yes [] No. Type of perforator used Factory Perforated Size of perforations 1/4 in. by three in. 720 perforations from 380 ft. to 440 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 305 ft. below land surface Date 3/16/70 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [x] No Yield: 50 gal./min. with ft. drawdown after hrs. Two hr. Air Test yield 50 gpm Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date Temperature of water 58 Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION:

Well seal—Material used Cement Grout Depth of seal 21' ft. Diameter of well bore to bottom of seal 14" for 10" casing cemented to 6" Depth 104' Were any loose strata cemented off? [] Yes [] No Was a drive shoe used? [] Yes [x] No Did any strata contain unusable water? [] Yes [x] No Type of water depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Wasco Driller's well number One NE 1/4 SW 1/4 Section 3 T. 45 R. 12 E.W.M. Bearing and distance from section or subdivision corner 1612" North, 387" West from 1/4 c/comon to Section 3 and Section 10

(12) WELL LOG:

Diameter of well below casing Depth drilled 500 ft. Depth of completed well 500 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Soil, Br., Loam; Clay, Brown; Gravel, Fine, Br., Clay; Gravel, Coarse, Br., Clay; Basalt, Blk.; Basalt, Brown, Soft; Clay, Red; Gravel, Coarse, Clay, Br.; Basalt, Brown.

Work started March 11 19 70 Completed 3-16-19 70 Date well drilling machine moved off of well 3-17-70 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Don Parry ik Date 3-17-19 70 (Drilling Machine Operator)

Drilling Machine Operator's License No. 640

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. NAME PROJECT: Corporation (Person, firm or corporation) (Type or print) Address 1 So. 2nd, Walla Walla, Wn. 99362 [Signed] Gary Hisey ik (Water Well Contractor) Contractor's License No. 527 Date 4-1-19 70